

# ABB4100R7W



Ind. P&S#ABB4100R7W

## General Information

Extended Product Type	ABB4100R7W
Product ID	2CMA100413R1000
EAN	7392696004138
Catalog Description	Ind. P&S#ABB4100R7W
Long Description	IEC Receptacle 100A 3P4W 3phase 480V Clock Position Of Grounding Contact 7 hour Color code Red

## Ordering

EAN	7392696004138
Minimum Order Quantity	1 piece
Country of Origin	Czech Republic (CZ)

## Dimensions

Product Net Width	135 mm
Product Net Height	200 mm
Product Net Length	140 mm
Product Net Weight	1.14 kg

## Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.82 kg
Package Level 1 EAN	7392696004138
Package Level 1 Units	1 piece
Package Level 2 Units	174 piece

## Technical UL/CSA

Ampere Rating UL/CSA	100 A
----------------------	-------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0020
Declaration	2CMC700005D0020
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0020
UL Certificate	E163435-19950105-UL_cert_C_R

---

## Additional Information

Additional Information	3P+E
Cable Cross-Section	16 ... 70 mm <sup>2</sup>
Color	Red
Connection Type	Screw clamp
Degree of Protection	IP67 IP69
Enclosure Material	Thermoplastic polyester (PBT)
Frequency (f)	50 Hz 60 Hz
Function	Receptacle
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB4100R7W
Mounting Holes	71x71
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TR
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	100 A
Rated Voltage (U <sub>r</sub> )	480 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13

---

## Classifications

eClass	27440504
UNSPSC	39120000

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

