

# ABB530P7W



Ind. P&S#ABB530P7W

## General Information

Extended Product Type	ABB530P7W
Product ID	2CMA100344R1000
EAN	7392696003445
Catalog Description	Ind. P&S#ABB530P7W
Long Description	IEC Plug 30A 4P5W 3phase-Y 277/480V Clock Position Of Grounding Contact 7 hour Color code Red

## Ordering

EAN	7392696003445
Minimum Order Quantity	1 piece
Country of Origin	Czech Republic (CZ)

## Dimensions

Product Net Width	101 mm
Product Net Height	101 mm
Product Net Length	188 mm
Product Net Depth / Length	188 mm
Product Net Weight	0.22 kg

## Container Information

Package Level 1 Width	114 mm
Package Level 1 Depth / Length	114 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	0.22 kg
Package Level 1 EAN	7392696003445
Package Level 1 Units	1 piece
Package Level 2 Units	171 piece

## Technical UL/CSA

Ampere Rating UL/CSA	30 A
----------------------	------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0020
Declaration	2CMC700005D0020
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0020
UL Certificate	E109550-19950105-UL_cert_P_B

## Additional Information

Additional Information	3P+N+E
Cable Cross-Section	2.5 ... 6 mm <sup>2</sup>
Color	Red
Connection Type	Screw clamp
Degree of Protection	IP67 IP69
Enclosure Material	Thermoplastic polyester (PBT)
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB530P7W
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	30 A
Rated Voltage (U <sub>r</sub> )	277/480 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13

## Classifications

eClass	27440509
UNSPSC	39120000

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

