



Monitoring Relays T&B Catalog Number:

1SVR750660R0200

UPC Number:

80432558495

Status:

Active

Description:

Insulation monitoring relay for ungrounded 0-400 VAC and 0-600 VDC systems with a maximum leakage capacitance of 20 microfarads and 24-240V AC/DC control supply voltage

Features

Two measuring ranges 1-100 kilohms and 2-200 kilohms

Selectable normally energized or normally de-energized

Non-volatile fault storage configurable

Application

Insulation monitoring relays for ungrounded IT installations

General

Series	CM-N
Output Contacts	2 SPDT
Operation-Function	Insulation Monitor

Dimension Information

L x W x D (inches)	3.07 x 1.77 x 3.94
--------------------	--------------------

Specifications

Input Voltage (AC)	0-400
Input Voltage (DC)	0-600
Supply Voltage (AC)	24-240
Supply Voltage (DC)	24-240
LED Indicator	3
Time Delay	0.1 sec - 30 secs. Adjustable

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	64.5 lbs. per 100

Certifications

Approvals	CE
-----------	----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com