

Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Selector switch operators

Selection and ordering data



Version	Key removal position	Lock No.	Cam Code 1)	Order no.	Weight approx. lbs.	Pack unit
Key-operated selector Switches with 2 switching positions						
Maintained operation	Both	501CH	A	52SC6AE		1
	Left	501CH	A	52SC6AF		
Key-operated selector Switches with 3 switching positions						
Maintained operation	All	501CH	B	52SC6BE		1
			C ²⁾	52SC6CE		
	Left	501CH	D	52SC6DE		1
			E	52SC6EE		
			G	52SC6GE		
	Right	501CH	B	52SC6BF		1
			C ²⁾	52SC6CF		
			D	52SC6DF		
	Center	501CH	E	52SC6EF		1
			G	52SC6GF		
			B	52SC6BG		
	Left and right	501CH	C ²⁾	52SC6CG		1
			D	52SC6DG		
			E	52SC6EG		
	Left and center	501CH	G	52SC6GG		1
			B	52SC6BH		
			C ²⁾	52SC6CH		
	Right and center	501CH	D	52SC6DH		1
			E	52SC6EH		
			G	52SC6GH		
	Left and right	501CH	B	52SC6BJ		1
			C ²⁾	52SC6CJ		
			D	52SC6DJ		
	Left and center	501CH	E	52SC6EJ		1
			G	52SC6GJ		
			B	52SC6BK		
	Right and center	501CH	C ²⁾	52SC6CK		1
			D	52SC6DK		
			E	52SC6EK		
	Left and right	501CH	G	52SC6GK		1
			B	52SC6BM		
			C ²⁾	52SC6CM		
	Center	501CH	D	52SC6DM		1
			E	52SC6EM		
			G	52SC6GM		
Spring return from right operation	Center	501CH	B	52SC6BU		1
			C ²⁾	52SC6CU		
			D	52SC6DU		
	Left and center	501CH	E	52SC6EU		1
			G	52SC6GU		
			B	52SC6BZ		
	Center	501CH	C ²⁾	52SC6CZ		1
			D	52SC6DZ		
			E	52SC6EZ		
	Left and right	501CH	G	52SC6GZ		1
			B	52SC6BT		
			C ²⁾	52SC6CT		
	Center	501CH	D	52SC6DT		1
			E	52SC6ET		
			G	52SC6GT		
	Right	501CH	B	52SC6BW		1
			C ²⁾	52SC6CW		
			D	52SC6DW		
	Center and right	501CH	E	52SC6EW		1
			G	52SC6GW		
			B	52SC6BY		
	Center	501CH	C ²⁾	52SC6CY		1
			D	52SC6DY		
			E	52SC6EY		
	Left and right	501CH	G	52SC6GY		1
			B	52SC6BV		
			C ²⁾	52SC6CV		
	Center	501CH	D	52SC6DV		1
			E	52SC6EV		
			G	52SC6GV		

Lock types keyed different from standard - up to 25 per order
To order special locks for keyed selector switches, append corresponding 'X' suffix to part number.

Ordering example
52SC6AEX298

1) For contact operation, see cam selection chart on page 10/123.

2) C cam limited to 4 single or double pole blocks on spring return operators

#550CH
#549CH
#548CH
#547CH
#506CH

X298
X299
X300
X301
X302

1