



POWER SUPPLY; PHASES:1; PN(KW):0,084;  
 UPRI(V):230-115; USEC(V DC):24; ISEC(A DC):3,5/4,2  
 (60/40 CEL); F(HZ):50...60; VECTOR GR./SHIELD  
 WNG.:II0 /0; PROTECTION CL.:I; TA/ISOKL:60 /B;  
 W(%):5; IP00; TYPE OF TERMINALS:SCREW/TAB  
 CONNECTION; INSTALLATION:MOUNTING RAILS;  
 EN 61558-2-6, EN61131-2 >SAFETY ISOLATING  
 TRANSFORMER<

General technical data		
Product designation		<a href="#">4AV2302-2EB00-0A</a>
Product brand name		SIDAC
Vector group		II0
Certificate of suitability		CE / cRUus
Product function		
<ul style="list-style-type: none"> <li>• Temperature monitoring</li> </ul>		No
<ul style="list-style-type: none"> <li>• Insulation monitoring</li> </ul>		No
<ul style="list-style-type: none"> <li>• Short-circuit and overload proof</li> </ul>		Yes
<ul style="list-style-type: none"> <li>• varistor protective wiring</li> </ul>		Yes
Operating resource protection class		I
Number of shielding windings		0
Inputs		
Phase number of the inputs		1
Type of current of the inputs		AC
Input voltage		
<ul style="list-style-type: none"> <li>• _1 rated value</li> </ul>	V	230
<ul style="list-style-type: none"> <li>• _2 rated value</li> </ul>	V	115

<b>Electrical input frequency</b>		
• minimum	Hz	50
• maximum	Hz	60
<b>Input voltage</b>		
• minimum	V	103.5
• maximum	V	243.8
<b>Input current</b>		
• _1 rated value	A	0.63
• _2 rated value	A	1.3
<b>Type of electrical connection at input for main current circuit</b>		screw-type terminals / tab terminals

<b>Outputs</b>		
<b>Type of current</b>		
• _1 at output		DC
<b>Output voltage</b>		
• _1 rated value	V	24
<b>Output voltage of the measurement signal at analog output at DC maximum</b>	V	28.8
<b>Output voltage of the measurement signal at analog output at DC minimum</b>	V	20.4
<b>Output current</b>		
• _1 rated value	A	3.5
<b>Type of electrical connection at output for main current circuit</b>		screw-type terminals / tab terminals
<b>Relative residual ripple</b>		
• of the output voltage 1 for main current circuit maximum	%	5

<b>Ambient conditions</b>		
<b>Thermal class acc. to IEC 60085</b>		B
<b>Ambient temperature rated value</b>	°C	60
<b>Protection class IP</b>		IP00

<b>Mechanical data</b>		
<b>Mounting type</b>		standard rail
<b>Construction form of the iron core</b>		EI 66-88/41
<b>Width</b>	m	0.072
<b>Height</b>	m	0.136
<b>Depth</b>	m	0.111

**Certificates/ approvals**

General Product Approval	Declaration of Conformity	Shipping Approval	other
--------------------------	---------------------------	-------------------	-------



[Miscellaneous](#)



[Confirmation](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AV2302-2EB00-0A>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AV2302-2EB00-0A>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/4AV2302-2EB00-0A>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=4AV2302-2EB00-0A&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AV2302-2EB00-0A&lang=en)

last modified:

03/05/2020