





Supplementary Protectors AC/DC Product Range

5SY5 70 mm mounting depth

Features

- U_n : 230/400 V, 50-60 Hz, 220 V DC per pole, applicable in networks up to: 250/440 V AC
 - 220 V DC: 1-pole
 - 440 V DC: 2-pole
- Standards: EN 60 898-2, DIN VDE 0641 Part 12, IEC 60 898-2
- Additional components can be retrofitted.
- Devices do not comply with UL1077

Selection and ordering data

	I_n	MW	Characteristic B		Characteristic C		Weight 1 item kg	Pack. unit Items
			Order No.	Price 1 item	Order No.	Price 1 item		
 <p>1-pole</p> 	A							
	0.3	1	-		5SY5 114-7		0.147	12
	0.5		-		5SY5 105-7			
	1		-		5SY5 101-7			
	1.6		-		5SY5 115-7			
	2		-		5SY5 102-7			
	3		-		5SY5 103-7			
	4		-		5SY5 104-7			
	6		5SY5 106-6		5SY5 106-7			
	8		-		5SY5 108-7			
	10		5SY5 110-6		5SY5 110-7			
	13		5SY5 113-6		5SY5 113-7			
	16		5SY5 116-6		5SY5 116-7			
	20		5SY5 120-6		5SY5 120-7			
	25		5SY5 125-6		5SY5 125-7			
	32 ¹⁾		5SY5 132-6		5SY5 132-7			
40		5SY5 140-6		5SY5 140-7				
50		5SY5 150-6		5SY5 150-7				
63		5SY5 163-6		5SY5 163-7				
 <p>2-pole</p> 	A							
	0.3	2	-		5SY5 214-7		0.304	6
	0.5		-		5SY5 205-7			
	1		-		5SY5 201-7			
	1.6		-		5SY5 215-7			
	2		-		5SY5 202-7			
	3		-		5SY5 203-7			
	4		-		5SY5 204-7			
	6		5SY5 206-6		5SY5 206-7			
	8		-		5SY5 208-7			
	10		5SY5 210-6		5SY5 210-7			
	13		5SY5 213-6		5SY5 213-7			
	16		5SY5 216-6		5SY5 216-7			
	20		5SY5 220-6		5SY5 220-7			
	25		5SY5 225-6		5SY5 225-7			
	32		5SY5 232-6		5SY5 232-7			
40		5SY5 240-6		5SY5 240-7				
50		5SY5 250-6		5SY5 250-7				
63		5SY5 263-6		5SY5 263-7				

1 MW = modular width of 18 mm
Depth 70 mm = device mounting depth of 70 mm