

CIRCUIT BREAKER 400V 10KA, 3-POLE, D, 6A, D=70MM



Model	
product brandname	SENTRON
Product designation	Miniature circuit breaker
General technical data	
Number of poles	3
Number of poles / Note	3P
Tripping characteristic class	D
characteristic / Let-through current characteristic	DS_5SY_D_6
circuit-breaker / Design	5SY4
Mechanical service life (switching cycles) / typical	20 000
Overvoltage category	3
Voltage	
Type of voltage	AC/DC
Insulation voltage	440 V
<ul style="list-style-type: none"> <li>with multi-phase operation / at AC / rated value</li> </ul>	440 V
Supply voltage	
Supply voltage / at AC / rated value	400 V
Supply voltage frequency	

- rated value

50/60 Hz

### Protection class

<b>Protection class IP</b>	IP20, with connected conductors
<b>Energy limiting class</b>	3

### Switching capacity

<b>Switching capacity current</b>	
<ul style="list-style-type: none"> <li>• at DC / acc. to IEC 60947-2 / rated value</li> </ul>	15 kA
<ul style="list-style-type: none"> <li>• acc. to EN 60898 / rated value</li> </ul>	10 kA
<ul style="list-style-type: none"> <li>• acc. to IEC 60947-2 / rated value</li> </ul>	35 kA

### Dissipation

<b>Power loss [W]</b>	
<ul style="list-style-type: none"> <li>• for rated value of the current / at AC / in hot operating state / per pole</li> </ul>	1.6 W
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	4.8 W

### Electricity

rated current $I_n$ / IEC, DIN/VDE / at 40 Cel	5.7 A
Current / at AC / rated value	6 A
<b>Current limitation characteristic, no. / Let-through energy</b>	DE_5SY_D_6

### Product details

Product feature / Touch protection	Yes
<b>Product component</b>	
<ul style="list-style-type: none"> <li>• combined terminal top</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• combined terminal bottom</li> </ul>	Yes
<b>Product feature</b>	
<ul style="list-style-type: none"> <li>• Properties for main switches in accordance with EN 60204-1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• halogen-free</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• sealable</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• silicon-free</li> </ul>	Yes
Product extension / can be installed / supplementary devices	Yes

### Product function

Product function / neutral conductor switching	No
--	----

### Short circuit

<b>Breaking capacity short-circuit current (<math>I_{cn}</math>)</b>	
<ul style="list-style-type: none"> <li>• at AC / acc. to UL 1077 and CSA C22.2 No.235</li> </ul>	5 kA

### Number

<b>Number of test cycles / for environmental testing / acc. to IEC 60068-2-30</b>	6
---	---

Connections	
<b>Connectable conductor cross-section / stranded</b>	
• minimum	0.75 mm <sup>2</sup>
• maximum	35 mm <sup>2</sup>
<b>Connectable conductor cross-section</b>	
• solid	
— minimum	0.75 mm <sup>2</sup>
— maximum	35 mm <sup>2</sup>
• finely stranded / with core end processing	
— minimum	0.75 mm <sup>2</sup>
— maximum	25 mm <sup>2</sup>
<b>AWG number / as coded connectable conductor cross section</b>	
• minimum	14
• maximum	4
<b>Tightening torque [lbf·in] / with screw-type terminals</b>	
• minimum	22 lbf·in
• maximum	26 lbf·in
<b>Tightening torque / with screw-type terminals</b>	
• minimum	2.5 N·m
• maximum	3 N·m
Position / of power supply cord	Any
Mechanical Design	
<b>Height</b>	90 mm
<b>Width</b>	54 mm
<b>Depth</b>	76 mm
<b>Mounting position</b>	any
<b>Installation depth</b>	70 mm
<b>Number of width units</b>	3
<b>Mounting type</b>	Quick assembly system
<b>Net weight</b>	465 g
Environmental conditions	
<b>Influence of the surrounding temperature</b>	Max. 95% humidity
Vibration resistance / acc. to IEC 60068-2-6	50m/s <sup>2</sup> at 25 to 150Hz and 60m/s <sup>2</sup> at 35Hz (4sec)
<b>Ambient temperature</b>	
• minimum	-25 °C
• maximum	55 °C
• during storage / minimum	-40 °C
• during storage / maximum	75 °C
Certificates	
Equipment marking / acc. to DIN EN 61346-2	F

## General Product Approval



CCC



IMQ



UL



VDE



RCM

[sonstig](#)

Declaration of  
Conformity

Test Certificates

Shipping Approval



EG-Konf.

[spezielle  
Prüfbescheinigunge  
n](#)

[sonstig](#)



ABS



BUREAU  
VERITAS

Lloyd's  
Register

LRS

## Shipping Approval



RINA

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SY4306-8>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5SY4306-8/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SY4306-8](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY4306-8)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>





