



NEMA Contact Block 3NO / 1NC
Side Mounted Screw Terminal
Size 00-4 for Contactors/Starters
For use on class 14, 22, 30, 40, and 43 Contactors/Starters



Image is representative and may not depict the actual product.

| General technical data: | |
|-----------------------------------|--|
| Weight | .070 lb |
| Height x Width x Depth | 2.70 x 1.16 x 3.10 in. |
| Finger-safe | No |
| Maximum altitude | 6560 ft |
| Ambient storage temperature | (-55 to 80)°C / (-67 to 176)°F |
| Ambient operating temperature | (-35 to 75)°C / (-31 to 167)°F |
| Humidity (% non-condensing) | (no data) |
| Rated impulse voltage resistance | (no data) |
| Rated insulation voltage | (no data) |
| Country of origin | Mexico |
| Acceptability for application | Control Power Relay |
| Number of NC contacts | 1 |
| Number of NO contacts | 3 |
| Operating Current at A600: | |
| Continuous current | 10A |
| 120 VAC | 60A Make / 6A Break |
| 240 VAC | 30A Make / 3A Break |
| 480 VAC | 15A Make / 1.5A Break |
| 600 VAC | 12A Make / 1.2A Break |
| Voltamperes | 7200 Make / 720 Break |
| Operating Current at P600: | |
| Continuous current | 5.0A |
| 125 VDC | 1.1A Make / 1.1A Break |
| 250 VDC | 0.55A Make / 0.55A Break |
| 301 to 600 VDC | 0.20A Make / 0.20A Break |
| Voltamperes | 138 Make / 138 Break |
| Mounting/wiring: | |
| Mounting orientation | Side |
| Mounting type | Snap-on mounting |
| Connection type / torque | Screw / 7-10 in-lb |
| Solid & stranded conductors | 1x(10-20 AWG or 2x(14-22 AWG) CU 75°C |
| Certificates/approvals: | |
| | UL (file no. E14900) |
| | cUL (file no. E14900 for Canada) |
| | CSA (file no. LR 6535) |
| | ISO 9001 certification |
| Additional information: | |
| | Instruction Sheet |

