

Selector switch, metal Maintained, long lever 1NO-1NC left, right position, A Cam 2 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Enclosure	
Number of command points	1
Delivery state	
<ul style="list-style-type: none"> as a kit 	No
Actuator	
Material of the actuating element	plastic
Number of contact modules	1
Type of unlocking device	rotate-to-unlatch mechanism
Number of switching positions	2
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
General technical data	
Product function	
<ul style="list-style-type: none"> positive opening 	Yes
Product component	
<ul style="list-style-type: none"> Light source 	No
Insulation voltage	
<ul style="list-style-type: none"> rated value 	600 V
Protection class IP	
<ul style="list-style-type: none"> of the terminal 	IP66 IP20
Operating frequency maximum	600 1/h
Thermal current	10 A
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	1
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	
<ul style="list-style-type: none"> at 110 V rated value at 500 V rated value 	60 A 12 A
Connections/ Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m

Tightening torque [lbf·in]	
<ul style="list-style-type: none"> with screw-type terminals 	8 lbf·in
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operation during storage 	<p>-35 ... +70 °C</p> <p>-40 ... +85 °C</p>
Installation/ mounting/ dimensions	
Shape of the installation opening	round
Certificates/ approvals	
Further information	
Information- and Downloadcenter (Catalogs, Brochures,...) www.siemens.com/sirius/catalogs	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2AABA1	
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SB2AABA1	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2AABA1	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2AABA1&lang=en	
last modified:	11/13/2019