

Keyed selector switch, metal Maintained G Cam 3 position Operator only Non-Illuminated Key type 501CH (standard) Key removable in all positions UL file E22655 in Vol. 6 (7) Sec. 13 (2)

| | |
|-----------------------|----------------|
| Design of the product | Actuator round |
|-----------------------|----------------|

Enclosure

| | |
|--|----|
| Number of command points | 1 |
| Delivery state | No |
| <ul style="list-style-type: none"> as a kit | No |

Actuator

| | |
|-------------------------------------|-----------------------------|
| Design of the operating mechanism | Key-operated switch |
| Material of the actuating element | metal |
| Type of unlocking device | key unlatching |
| Number of switching positions | 3 |
| Switch position for key distraction | removable in every position |
| Lock make | ILLINOIS |
| Key number | 501CH |

Front ring

| | |
|------------------------------|----------|
| Product component front ring | Yes |
| Design of the front ring | standard |
| Material of the front ring | metal |
| Color of the front ring | chrome |

Holder

| | |
|------------------------|-------|
| Material of the holder | Metal |
|------------------------|-------|

General technical data

| | |
|--|---------|
| Product component | No |
| <ul style="list-style-type: none"> Light source | No |
| Degree of pollution | 1 |
| Protection class IP | IP66 |
| Operating frequency maximum | 600 1/h |

Ambient conditions

| | |
|--|----------------|
| Ambient temperature | -35 ... +70 °C |
| <ul style="list-style-type: none"> during operation | -35 ... +70 °C |
| <ul style="list-style-type: none"> during storage | -40 ... +85 °C |

Installation/ mounting/ dimensions

| | |
|-----------------------------------|-------|
| Shape of the installation opening | round |
|-----------------------------------|-------|

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6GE>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6GE>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6GE>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6GE&lang=en

last modified:

11/13/2019