



## Locking Heads T&B Catalog Number:

TYD-LH  
78621071339  
Active

**UPC Number:**  
**Status:**  
**Description:**

Cable Tie Deltec 25 Heads Only

### Features

Perfect for coaxial, fiber optic and all other communication and electrical conducting cables.

Strap and body are weatherable acetal, offering superior resistance to sunlight, moisture and salt environments.

Locking device is marine-grade corrosion-resistant copper alloy.

### Application

Ideal solution for bundling in harsh outdoor environments.

### General

Material Weather-Resistant Acetel  
Color Black

### Specifications

Temperature Rating -30°F to 150°F

### Tooling

Application Tools WT3D

### Packaging

T&B Order Multiple 25  
T&B Inner Pack 25  
Package in Units 125  
Package Type Regular  
T&B Sold in UOM Each  
T&B Weight Per UOM 0.96 lbs. per 100

### Application Support

Overview Available on Website  
Material Selection Guide Available on Website

### Notes

The recommended maximum continuous static loading for the Deltec® straps is 20 lbs. Per strap. For best results suggested spacing is 15 inches. It is the responsibility of the user to determine whether or not their application meets our recommendation.

### Certifications

RoHS Compliance Yes

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289

