



Family

**Catalog Number:** VCSG-48B.30  
**Product ID:** 7TAA292240R0238  
**UPC Number:** 78620997698  
**EAN Number:** 07630030284342  
**Status:** Active

Coarse Profile Heavy Wall Flexible Black Conduit, (VCS) Material - Polyamide 6, Conduit Size NW - 48, 30 Meters

- Very good resistance to ultra violet (UV) rays and weathering
- Good flexibility
- High compression and impact strengths at low temperature and low humidity
- Self-extinguishing
- Free from halogens and cadmium
- Free from halogens and cadmium
- External applications, static installations in railway vehicles

### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Heavy Duty Conduit
Application	Rail
Standard	CSA
Trade Size	NW48
Outside Diameter	2.15 Inch
Length	30 m
Flexibility	Medium Flexibility
Material	Polyamide/Nylon 6
Color	Black

### European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	50mm
Outer diameter	54.4mm
Inner diameter	46.8mm
Material	Polyamide 6
Compressive strength	300N
Operating temperature	-50 - +105°C
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	N
Halogen free	Y
Approved according to DIN EN 61386-23	Y
Approved according to UR	Y
Approved according to CSA	Y
Approved according to LUL/British Standard	Y
Approved according to Lloyd's Register TA	Y
Approved according to UTAC	N
Approved according to DIN 5510	Y

Approved according to NF F 16-101 Y

## Packaging

Inner Quantity	1
Outer Dimensions (inches)	47.244x31.496x30.709
Weight Uom	0.51 lbs. Each

## Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

### For further technical assistance, please contact us...

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com