

WIRE CONNECTOR LARGE WITH CONTROL WIRE TAP 3 PCS.
ACCESSORY FOR: 3VA4/5 125



Model	
Product brand name	SETRON
Product designation	accessories
Design of the product	circular conductor terminal
Connections according IEC	
IEC-marking / of terminals	25-150 mm ² CU/AL NNL
Connectable conductor cross-section	
<ul style="list-style-type: none"> • for copper cable / finely stranded / minimum 	25 mm ²
<ul style="list-style-type: none"> • for copper cable / finely stranded / maximum 	120 mm ²
<ul style="list-style-type: none"> • for copper cable / stranded / minimum 	25 mm ²
<ul style="list-style-type: none"> • for copper cable / stranded / maximum 	150 mm ²
<ul style="list-style-type: none"> • for aluminum cable / stranded / minimum 	25 mm ²
<ul style="list-style-type: none"> • for aluminum cable / stranded / maximum 	150 mm ²
Wire stripping length	30,5 mm
Tightening torque / when using copper cables	
<ul style="list-style-type: none"> • stranded 	29 Nm






- finely stranded

29 Nm

Connections according UL

UL-marking / of terminals	TA2.1 CMC 4-300 CU7AL UR CSA
Permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C
Wire stripping length	1.2 in
Connectable conductor cross-section <ul style="list-style-type: none"> • for copper cable / stranded / minimum • for copper cable / stranded / maximum • for copper cable / finely stranded / minimum • for copper cable / finely stranded / maximum • for aluminum cable / stranded / minimum • for aluminum cable / stranded / maximum 	4 AWG 300 kcmil 4 AWG 300 kcmil 4 AWG 300 kcmil
Tightening torque / when using copper cables <ul style="list-style-type: none"> • stranded • finely stranded 	255 lb-in 255 lb-in

Certificates

General Product Approval	EMC	Declaration of Conformity	other
			
			Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9133-0JC12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9133-0JC12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)







http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9133-0JC12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

01/12/2018