

SIPLUS ET 200S TM-E15C24-01 -40...+70°C with conformal coating based on 6ES7193-4CB30-0AA0 5 units per packing unit . for electronic modules 15 mm width, spring-type terminals 2x4 terminal connections without terminal access to AUX1, AUX1 continuous



Figure similar

### Standards, approvals, certificates

CE mark	Yes
---------	-----

### Ambient conditions

#### Ambient temperature during operation

• min.	-40 °C; = Tmin
• max.	70 °C; = Tmax

#### Altitude during operation relating to sea level

• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

#### Relative humidity

• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
---	--

#### Resistance

Use in stationary industrial systems

- to biologically active substances according to EN 60721-3-3
- to chemically active substances according to EN 60721-3-3
- to mechanically active substances according to EN 60721-3-3

Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request

Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*

Yes; Class 3S4 incl. sand, dust, \*

**Use on ships/at sea**

- to biologically active substances according to EN 60721-3-6
- to chemically active substances according to EN 60721-3-6
- to mechanically active substances according to EN 60721-3-6

Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request

Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*

Yes; Class 6S3 incl. sand, dust; \*

**Remark**

- Note regarding classification of environmental conditions acc. to EN 60721

\* The supplied plug covers must remain in place over the unused interfaces during operation!

**Dimensions**

Width	15 mm
Height	132 mm
Depth	43 mm

**Weights**

Weight, approx.	65 g
-----------------	------

**Scope of supply**

Delivery quantity in pieces	5
-----------------------------	---

**last modified:** 05/30/2019