

30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Indicator Light Full Voltage type, 120V AC/DC Incandescent Lamp, BA9s Plastic Lens, Red UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Figure similar

<b>Product brand name</b>	Siemens Pilot Devices
<b>Design of the product</b>	Complete Unit, Round
<b>Enclosure</b>	
<b>Number of command points</b>	1
<b>Delivery state</b>	No
• as a kit	
<b>Actuator</b>	
<b>Design of the operating mechanism</b>	Indicator Light
<b>Product extension optional Light source</b>	Yes
<b>Color</b>	
• of the actuating element	red
<b>Material of the actuating element</b>	plastic
<b>Shape of the actuating element</b>	Concentric rings
<b>Front ring</b>	
<b>Product component front ring</b>	Yes
<b>Design of the front ring</b>	standard
<b>Material of the front ring</b>	metal

<b>Color of the front ring</b>	black
<b>Holder</b>	
<b>Material of the holder</b>	metal
<b>Contact block/ lampholder</b>	
<b>Mounting type</b>	BA 9s, with incandescent lamp
<b>Number of lampholders</b>	1
<b>Display</b>	
<b>Number of LED modules</b>	0
<b>General technical data</b>	
<b>Product component</b>	
• lamp transformer	No
• Light source	Yes
<b>Degree of pollution</b>	1
<b>Type of voltage</b>	
• of the operating voltage	AC/DC
• of the input voltage	AC/DC
<b>Surge voltage resistance rated value</b>	4 kV
<b>Protection class IP</b>	IP66
• of the terminal	IP20
<b>Mechanical service life (switching cycles)</b>	
• typical	5
<b>Supply voltage</b>	
<b>Type of voltage of the supply voltage</b>	
• of the light source	AC/DC
<b>Supply voltage of the light source at AC</b>	
• at 60 Hz rated value	120 V
<b>Supply voltage of the light source at DC</b>	
• rated value	120 V
<b>Connections/Terminals</b>	
<b>Type of electrical connection</b>	screw-type terminals
• of modules and accessories	screw-type terminals
<b>Type of connectable conductor cross-sections</b>	
• at AWG conductors for auxiliary contacts	1x (18 ... 12), 2x (18 ... 16), 2x (16 ... 14), 2x 12
<b>Tightening torque of the screws in the bracket</b>	20 N·m
<b>Tightening torque [lbf·in]</b>	
• with screw-type terminals	8 ... 8 lbf·in
<b>Lamp</b>	
<b>Type of light source</b>	Incandescent
<b>Color of the light source</b>	clear

## Safety related data

<b>Protection against electrical shock</b>	finger safe
--	-------------

## Ambient conditions

<b>Ambient temperature</b>	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C

## Installation/ mounting/ dimensions

• Mounting type of modules and accessories	screw-mounting
<b>Shape of the installation opening</b>	round

## Certificates/approvals

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BL4E2>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BL4E2>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52BL4E2>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52BL4E2&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BL4E2&lang=en)

last modified:

06/13/2019