SIEMENS

Data sheet

US2:52BP2V2

30mm BlackMax, Epoxy Coated Corrosion Resistant Metal Operator, Round Push-Pull Operator Non-Illuminated Mushroom Head Cap Large 2 1/2" (63.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Figure similar

Design of the product	Actuator round	
Enclosure		
Number of command points	1	
Delivery state		
● as a kit	No	
Actuator		
Material of the actuating element	plastic	
Type of unlocking device	pull-to-unlatch mechanism	
Number of switching positions	2	
Front ring		
Product component front ring	Yes	
Design of the front ring	standard	
Material of the front ring	metal	
Color of the front ring	black	
Holder		
Material of the holder	Metal	

General technical data	
Product component	
Light source	No
Degree of pollution	1
Protection class IP	IP66
Ambient conditions	
Ambient temperature	
 during operation 	-35 +70 °C
 during storage 	-40 +85 °C
Installation/ mounting/ dimensions	
Shape of the installation opening	round
Certificates/approvals	
Further information	
Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/industrial-controls/catalogs	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2V2	
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2V2	
Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2V2	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP2V2⟨=en	

last modified:

05/08/2019