## **SIEMENS**

Data sheet	US2:52PP2A2
	30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Metal Operator, Round Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1.73" (44 mm) Metal, Anodized Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards
Design of the product	Actuator round
Enclosure	
Number of command points	1
Delivery state	
● as a kit	No
Actuator	
Material of the actuating element	metal
Type of unlocking device	pull-to-unlatch mechanism
Number of switching positions	2
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome
Holder	
Material of the holder	Metal
General technical data	
Product component	
Light source	No
Degree of pollution	1
Protection class IP	IP66
Ambient conditions	
Ambient temperature	
<ul><li>during operation</li></ul>	-35 +70 °C
during storage	-40 +85 °C
nstallation/ mounting/ dimensions	
Shape of the installation opening	round
Certificates/approvals	
Further information	
Information- and Downloadcenter (Catalogs, E http://www.siemens.com/industrial-controls/catalogs	Brochures,)

## Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2A2

## Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2A2

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2A2

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP2A2&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP2A2&lang=en</a>

**last modified:** 04/30/2019