

Metal, selector switch Spring return from right Short lever, 1NO-1NC left Right, 2 position position A cam, complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Enclosure

Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> • as a kit 	No

Actuator

Material of the actuating element	plastic
Number of contact modules	1
Type of unlocking device	without
Number of switching positions	2

Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal

General technical data

Product function	Yes
<ul style="list-style-type: none"> • positive opening 	Yes
Product component	No
<ul style="list-style-type: none"> • Light source 	No
Insulation voltage	600 V
<ul style="list-style-type: none"> • rated value 	600 V
Protection class IP	IP66
<ul style="list-style-type: none"> • of the terminal 	IP20
Operating frequency maximum	600 1/h
Thermal current	10 A

Auxiliary circuit

Number of NC contacts for auxiliary contacts	1
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	
<ul style="list-style-type: none"> • at 110 V rated value • at 230 V rated value • at 400 V rated value • at 500 V rated value 	60 A 30 A 15 A 12 A

Connections/Terminals

Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	8 lbf·in
<ul style="list-style-type: none"> • with screw-type terminals 	

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-35 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C

Installation/ mounting/ dimensions

Shape of the installation opening	round
-----------------------------------	-------

Certificates/approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2ACBA1>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2ACBA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2ACBA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2ACBA1&lang=en

last modified:

05/04/2019