

Selector switch, metal Spring return left & right Long lever, no insert  
1NO-1NC left, right 3 Position, C Cam Complete device white insert  
Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

### Enclosure

<b>Number of command points</b>	1
<b>Delivery state</b>	No
<ul style="list-style-type: none"> <li>• as a kit</li> </ul>	No

### Actuator

<b>Material of the actuating element</b>	plastic
<b>Number of contact modules</b>	1
<b>Type of unlocking device</b>	without
<b>Number of switching positions</b>	3

### Front ring

<b>Product component front ring</b>	Yes
<b>Design of the front ring</b>	standard
<b>Material of the front ring</b>	metal

### General technical data

<b>Product function</b>	Yes
<ul style="list-style-type: none"> <li>• positive opening</li> </ul>	Yes
<b>Product component</b>	No
<ul style="list-style-type: none"> <li>• Light source</li> </ul>	No
<b>Insulation voltage</b>	600 V
<ul style="list-style-type: none"> <li>• rated value</li> </ul>	600 V
<b>Protection class IP</b>	IP66
<ul style="list-style-type: none"> <li>• of the terminal</li> </ul>	IP20
<b>Operating frequency maximum</b>	600 1/h
<b>Thermal current</b>	10 A

### Auxiliary circuit

<b>Number of NC contacts for auxiliary contacts</b>	1
<b>Number of NO contacts for auxiliary contacts</b>	1
<b>Operating current at AC-15</b>	
<ul style="list-style-type: none"> <li>• at 110 V rated value</li> <li>• at 230 V rated value</li> <li>• at 400 V rated value</li> <li>• at 500 V rated value</li> </ul>	60 A 30 A 15 A 12 A

### Connections/Terminals

Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	8 lbf·in
<ul style="list-style-type: none"> <li>• with screw-type terminals</li> </ul>	

#### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-35 ... +70 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +85 °C

#### Installation/ mounting/ dimensions

Shape of the installation opening	round
-----------------------------------	-------

#### Certificates/approvals

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2CDBA1>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SB2CDBA1>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2CDBA1>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SB2CDBA1&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2CDBA1&lang=en)

last modified:

05/02/2019