

Keyed selector switch, metal Maintained A Cam 2 position Operator only Non-Illuminated Key type 501CH (standard) Key removalble in all positions UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Design of the product	Actuator round
-----------------------	----------------

### Enclosure

Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> <li>as a kit</li> </ul>	No

### Actuator

Design of the operating mechanism	Key-operated switch
Material of the actuating element	metal
Type of unlocking device	key unlatching
Number of switching positions	2
Switch position for key distraction	removable in every position
Lock make	ILLINOIS
Key number	501CH

### Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome

### Holder

Material of the holder	Metal
------------------------	-------

### General technical data

Product component	No
<ul style="list-style-type: none"> <li>Light source</li> </ul>	No
Degree of pollution	1
Protection class IP	IP66
Operating frequency maximum	600 1/h

### Ambient conditions

Ambient temperature	-35 ... +70 °C
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-35 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C

### Installation/ mounting/ dimensions

Shape of the installation opening	round
-----------------------------------	-------

Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6AE>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6AE>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6AE>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SC6AE&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6AE&lang=en)

last modified:

04/30/2019