

Metal NEMA 4X, selector switch Maintained, long lever Position, H
Cam 4 position Operator only white insert Non-Illuminated UL file
E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

Design of the product	Actuator round
Enclosure	
Number of command points	1
Delivery state <ul style="list-style-type: none">• as a kit	No
Actuator	
Design of the operating mechanism	selector switch
Material of the actuating element	plastic
Shape of the actuating element	Extended handle
Type of unlocking device	rotate-to-unlatch mechanism
Number of switching positions	4
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	black

Holder	
Material of the holder	Metal
General technical data	
Product component	No
• Light source	
Degree of pollution	1
Protection class IP	IP66
Operating frequency maximum	600 1/h
Ambient conditions	
Ambient temperature	-35 ... +70 °C -40 ... +85 °C
• during operation	
• during storage	
Installation/ mounting/ dimensions	
Shape of the installation opening	round
Certificates/approvals	
Further information	
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SW2HAB	
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SW2HAB	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/US2:52SW2HAB	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SW2HAB&lang=en	
last modified:	04/30/2019