



Representative Image

Catalog No. 1SVR740712R1300

Description: CM-MSS.51P Therm. motor protec. relay 2x1c/o, 24-240VAC/DC

UPC No 4013614496554

Home > Electronic Relays & Controls > Measuring & Monitoring Relays

Descriptors

Category

Measuring & Monitoring Relays

Specifications

Product Line Type	Thermistor Motor Protection Relays
Function	2 sensor circuits Short-circuit detection, configurable Non-volatile fault storage, configurable Single or accumulative evaluation, configurable Dynamic interrupted wire detection Auto, manual or remote reset ATEX approved
Output	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Rated Control Supply Voltage	24 ... 240 V AC / DC
Terminal Type	Screwless Terminals
Product Main Type	CM-MSS
Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
RoHS Status	Following EU Directive 2011/65/EU
Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16AWG Rigid 2x 20-16 AWG
Object Classification Code	B

Classifications

ETIM 5.0	EC002568 - Temperature monitor (motor protection)
ETIM 6.0	EC002568 - Relay for thermistor protection (PTC)
ETIM 7	EC002568 - Relay for thermistor protection (PTC)
eClass	7.0 27371503

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm

Dimensions

Product Net Depth / Length	103.7 mm
Product Net Weight	0.135 kg

Package Information

Package Level 1 Units	1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	109 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Gross Weight	0.161 kg
Package Level 1 EAN	4013614496554

Ordering

Minimum Order Quantity	1
Customs Tariff Number	85364900
ECCN	N
ECN	N
ATEX Certificate	EU Type Examination Certificate_TPS_18_ATEX_044254_0018_X
ABB Business Unit	ELSP - Smart Power
ABB Product Group	3099>>ELSP