



Representative Image

## Catalog No. 1SVR730712R0200

Description: CM-MSS.32S Therm. motor protec. relay 2c/o, 24VAC/DC

UPC No 4013614496684

Home > Electronic Relays & Controls > Measuring & Monitoring Relays

### Descriptors

Category	Measuring & Monitoring Relays
----------	-------------------------------

### Specifications

Product Line Type	Thermistor Motor Protection Relays
Function	1 sensor circuit Short-circuit detection Dynamic interrupted wire detection Auto, manual or remote reset ATEX approved
Output	2 c/o (SPDT) contacts
Rated Control Supply Voltage	24 V AC / DC
Terminal Type	Screw Terminals
Product Main Type	CM-MSS
Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
RoHS Status	Following EU Directive 2011/65/EU
Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in·lb
Object Classification Code	B

### Classifications

ETIM 5.0	EC002568 - Temperature monitor (motor protection)
ETIM 6.0	EC002568 - Relay for thermistor protection (PTC)
ETIM 7	EC002568 - Relay for thermistor protection (PTC)
eClass	7.0 27371503

### Dimensions

Product Net Width	22.5 mm
-------------------	---------

## Dimensions

Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.13 kg

## Package Information

Package Level 1 Units	1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	109 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Gross Weight	0.157 kg
Package Level 1 EAN	4013614496684

## Ordering

Minimum Order Quantity	1
Customs Tariff Number	85364900
ECCN	N
ECN	N
ATEX Certificate	EU Type Examination Certificate_TPS_18_ATEX_044254_0018_X
ABB Business Unit	ELSP - Smart Power
ABB Product Group	3099>>ELSP