

**ACT20M-RTI-AO-E-S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****ACT20M: The slim solution**

- Safe and space-saving (6 mm) isolation and conversion
- Quick installation of the power supply unit using the CH20M mounting rail bus
- Easy configuration via DIP switch or FDT/DTM software
- Extensive approvals such as ATEX, IECEx, GL, DNV
- High interference resistance

**General ordering data**

|            |                                                                                               |
|------------|-----------------------------------------------------------------------------------------------|
| Version    | Temperature converter, Without galvanic isolation, Input : Temperature, PT100, Output : I / U |
| Order No.  | <a href="#">1375520000</a>                                                                    |
| Type       | ACT20M-RTI-AO-E-S                                                                             |
| GTIN (EAN) | 4050118259681                                                                                 |
| Qty.       | 1 pc(s).                                                                                      |

**ACT20M-RTI-AO-E-S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 114.3 mm | Depth (inches)  | 4.5 inch   |
| Height     | 112.5 mm | Height (inches) | 4.429 inch |
| Width      | 6.1 mm   | Width (inches)  | 0.24 inch  |
| Net weight | 86 g     |                 |            |

**Temperatures**

|                     |                |          |                                                |
|---------------------|----------------|----------|------------------------------------------------|
| Storage temperature | -40 °C...85 °C | Humidity | 40 °C / 93 % rel. humidity,<br>no condensation |
|---------------------|----------------|----------|------------------------------------------------|

**Probability of failure**

|      |           |
|------|-----------|
| MTBF | 195 Years |
|------|-----------|

**Environmental Product Compliance**

|            |                |      |                                      |
|------------|----------------|------|--------------------------------------|
| REACH SVHC | Lead 7439-92-1 | SCIP | 2f6dd957-421a-46db-a0c2-cf1609156924 |
|------------|----------------|------|--------------------------------------|

**Input**

|                                          |                                      |                         |                                                                                 |
|------------------------------------------|--------------------------------------|-------------------------|---------------------------------------------------------------------------------|
| Influence of the sensor cable resistance | < 0.002 $\Omega/\Omega$ (@ 3/4-wire) | Input measurement range | PT100 -200...+850 °C                                                            |
| Line resistance in measuring circuit     | $\leq 50 \Omega$                     | Number of inputs        | 1                                                                               |
| Sensor                                   | PT100 (2-/3-/4- wire)                | Temperature input range | Configurable, PT100:<br>-200...+850 °C, min.<br>measurement range 10°C<br>(RTD) |

**Output**

|                        |                                           |                        |                                                                 |
|------------------------|-------------------------------------------|------------------------|-----------------------------------------------------------------|
| Load impedance current | $\leq 600 \Omega$                         | Number of outputs      | 1                                                               |
| Output current         | configurable, 0...20 mA,<br>4...20 mA     | Output signal limit    | < 4 mA (average), < 60 mA<br>(pulse current), low duty<br>cycle |
| Output voltage, note   | configurable, 0(2)...10 V,<br>0(1)...5 V  | Type                   | active, connected control<br>must be passive                    |
| Wire break detection   | Yes, Configurable, 3.5 mA/<br>23 mA/ none | load impedance voltage | $\geq 10 \text{ k}\Omega$                                       |

**General data**

|                |                                                                                                                                                                                                               |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accuracy       | absolute accuracy: $\leq \pm 0.1$ % of the measurement range                                                                                                                                                  |
| Configuration  | DIP switch                                                                                                                                                                                                    |
| Delivery state | Output: 4...20 mA // Sensor error detection: enabled // Output error level: downscale //<br>Noise suppression: 50 Hz // Step response time: < 30 ms // Start temperature: -200 °C // End<br>temperature: 0 °C |

**ACT20M-RTI-AO-E-S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

**Technical data**

|                         |                                                    |                        |
|-------------------------|----------------------------------------------------|------------------------|
| Delivery state          | Setting parameters                                 | Output                 |
|                         | Configuration                                      | 4...20 mA              |
|                         | Setting parameters                                 | Sensor error detection |
|                         | Configuration                                      | enabled                |
|                         | Setting parameters                                 | Output error level     |
|                         | Configuration                                      | downscale              |
|                         | Setting parameters                                 | Noise suppression      |
|                         | Configuration                                      | 50 Hz                  |
|                         | Setting parameters                                 | Step response time     |
|                         | Configuration                                      | < 30 ms                |
|                         | Setting parameters                                 | Start temperature      |
|                         | Configuration                                      | -200 °C                |
|                         | Setting parameters                                 | End temperature        |
|                         | Configuration                                      | 0 °C                   |
| Galvanic isolation      | Without isolation                                  |                        |
| Power consumption, max. | 0.5 W                                              |                        |
| Power consumption, typ. | 0.37 W                                             |                        |
| Rail                    | TS 35                                              |                        |
| Step response time      | Configurable, ≤ 30 ms, < 300 ms                    |                        |
| Temperature coefficient | ≤ 0.01 % of the measurement range/°C or 0.02 °C/°C |                        |
| Type of connection      | Screw connection                                   |                        |
| Voltage supply          | 24 V DC ± 30 %                                     |                        |

**Insulation coordination**

|                    |                    |                    |                   |
|--------------------|--------------------|--------------------|-------------------|
| EMC standards      | IEC 61326-1, NE 21 | Galvanic isolation | Without isolation |
| Pollution severity | 2                  |                    |                   |

**Data for Ex applications (ATEX)**

|                       |                                       |         |                        |
|-----------------------|---------------------------------------|---------|------------------------|
| Installation location | Device installed in safe area, zone 2 | Marking | II 3 G Ex nA IIC T4 Gc |
|-----------------------|---------------------------------------|---------|------------------------|

**Connection data**

|                                         |                     |                                         |                     |
|-----------------------------------------|---------------------|-----------------------------------------|---------------------|
| Type of connection                      | Screw connection    | Tightening torque, min.                 | 0.4 Nm              |
| Tightening torque, max.                 | 0.6 Nm              | Clamping range, rated connection        | 2.5 mm <sup>2</sup> |
| Clamping range, min.                    | 0.5 mm <sup>2</sup> | Clamping range, max.                    | 2.5 mm <sup>2</sup> |
| Wire connection cross section AWG, min. | AWG 30              | Wire connection cross section AWG, max. | AWG 14              |

**EMC conformity and approvals**

|               |                    |           |             |
|---------------|--------------------|-----------|-------------|
| EMC standards | IEC 61326-1, NE 21 | Standards | IEC 61010-1 |
|---------------|--------------------|-----------|-------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002919    | ETIM 7.0    | EC002919    |
| ETIM 8.0    | EC002919    | ECLASS 9.0  | 27-21-01-29 |
| ECLASS 9.1  | 27-21-01-29 | ECLASS 10.0 | 27-21-01-29 |
| ECLASS 11.0 | 27-21-01-29 | ECLASS 12.0 | 27-21-01-29 |

**ACT20M-RTI-AO-E-S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Important note**

## Product information

The ACT20M-RTI-AO-S configurable temperature transducer isolates and converts analogue signals. An analogue RTD input signal (Type Pt100) is linearly converted into an analogue output signal and galvanically isolated. The power supply is galvanically isolated from the input and output (3-way isolation) and this is done with direct wiring or over the Weidmüller rail bus.

The ACT20M-RTI-AO-E-S configurable temperature transducer offers the same functionality but does not provide galvanic isolation.

**Approvals**

## Approvals



ROHS Conform

UL File Number Search UL Website

Certificate no. (cULus) E337701

**Downloads**

## Approval/Certificate/Document of Conformity

[DNV-GL certificate](#)  
[FM certificate](#)  
[IECEX certificate](#)  
[ATEX certificate](#)  
[Declaration of Conformity](#)

## Engineering Data

[CAD data – STEP](#)  
[EPLAN, WSCAD](#)

## Engineering Data

## Software

[Runtime Software – DIP switch configuration tool](#)

## User Documentation

[instruction sheet](#)

## Catalogues

[Catalogues in PDF-format](#)

## Brochures

www.weidmueller.com

[illegible][illegible]

5