


Data sheet | Item number: 216-102

Ferrule; Sleeve for 0.75 mm² / AWG 20; uninsulated; electro-tin plated; silver-colored



www.wago.com/216-102



Color: —

Data

Technical data

Main product function	Ferrule
Sleeve cross-section (AWG)	18 AWG

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Sleeve for	0.75 mm ²
------------	----------------------

Connection data

Strip length	8 mm / 0.31 inches
--------------	--------------------

Physical data

Length	8 mm
--------	------

Diameter	2.3 mm
----------	--------

Diameter 2	1.2 mm
------------	--------

Material data

Color	silver-colored
-------	----------------

Weight	0 g
--------	-----

Commercial data

Product Group	2 (Terminal Block Accessories)
---------------	--------------------------------

eCl@ss 10.0	27-40-02-01
-------------	-------------

eCl@ss 9.0	27-40-02-01
------------	-------------

ETIM 8.0	EC000005
----------	----------

ETIM 7.0	EC000005
----------	----------

PU (SPU)	5000 (1000) Stück
----------	-------------------

Packaging type	box
----------------	-----

Country of origin VKOrg Germany	DE
---------------------------------	----

GTIN	4017332277631
------	---------------

Customs tariff number VKOrg Germany	85369010000
-------------------------------------	-------------

Downloads

Documentation

Bid Text

216-102 X81 - Datei	Feb 19, 2019	xml 2.8 kB	Download
------------------------	--------------	---------------	----------

216-102 doc - Datei	Sep 11, 2017	doc 24.6 kB	Download
------------------------	--------------	----------------	----------

Subject to changes. Please also observe the further product documentation!



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 216-102

URL

Download

Ferrule; Sleeve for 0.75 mm² / AWG 20; uninsulated; electro-tin plated; silver-colored

Installation Notes



A perfect gas-tight crimp – both electrically and mechanically reliable

Subject to changes. Please also observe the further product documentation!