


B30 & B33 Series Materials

BradyID.com/s35

ToughWash® Washdown Resistant Labels (B-854, B-855)

- Withstands high pressure, heat, harsh chemicals and numerous washdown cycles
 - B-854 offers metal detectable layer to detect foreign debris in food stream
 - Legible and long-lasting for even the toughest washdown cycles
 - Ideal for use in the food & beverage industry
- Service Temp: -40°F to 230°F
Agency approvals: RoHS



Benchtop Printers

B30 Series

Fits Printer Model(s)	Diagram	Catalog #	B#	Color	Label Width A Inch (mm)	Length B Inch (mm)	Labels Per Roll	Rec. Ribbon
B-854 ToughWash™ Metal Detectable Material								
BBP30, 31, 33, 35, 37	Fig. 33	B30C-4000-854-YL	B-854		4.000 (101.06)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 33	B30C-4000-854-WT	B-854		4.000 (101.06)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-854-OSHADA	B-854		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-854-ANSIWA	B-854		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-854-ANSIDA	B-854		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-854-ANSICA	B-854		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-854-PEL	B-854		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-854-PREC	B-854		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
B-855 ToughWash™ Material								
BBP30, 31, 33, 35, 37	Fig. 33	B30C-1125-855-YL	B-855		1.125 (28.6)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 33	B30C-2250-855-YL	B-855		2.250 (57.5)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 33	B30C-4000-855-YL	B-855		4.000 (101.06)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 33	B30C-1125-855-WT	B-855		1.125 (28.6)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 33	B30C-2250-855-WT	B-855		2.250 (57.5)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 33	B30C-4000-855-WT	B-855		4.000 (101.06)	50ft. (15.2 m)	1 roll (cont.)	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-855-OSHADA	B-855		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-855-ANSIWA	B-855		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-855-ANSIDA	B-855		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-855-ANSICA	B-855		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-855-PEL	B-855		4.000 (101.06)	6.250 (158.8)	100	B30-R6000
BBP30, 31, 33, 35, 37	Fig. 73	B30-25-855-PREC	B-855		4.000 (101.06)	6.250 (158.8)	100	B30-R6000