

# DPE38G7

IEC contactor, Easy TeSys

DPE, nonreversing, 38A, 3P, 20HP at 480V

AC, 120V 50/60Hz coil



## Main

|                                |                                                                                                          |
|--------------------------------|----------------------------------------------------------------------------------------------------------|
| Range                          | Easy TeSys                                                                                               |
| Product name                   | Easy TeSys DPE                                                                                           |
| Product or Component Type      | Contactor                                                                                                |
| Device short name              | DPE                                                                                                      |
| Contactor application          | Resistive load<br>Motor control                                                                          |
| Utilisation category           | AC-4<br>AC-1<br>AC-3                                                                                     |
| Poles description              | 3P                                                                                                       |
| Maximum Operational Voltage    | Power circuit <= 690 V AC 25...400 Hz<br>Power circuit <= 300 V DC                                       |
| [Ie] rated operational current | 38 A 140 °F (60 °C) <= 440 V AC AC-3 power circuit<br>52 A 140 °F (60 °C) <= 440 V AC AC-1 power circuit |
| [Uc] control circuit voltage   | 120 V AC 50/60 Hz                                                                                        |

## Complementary

|                                             |                                                                                                                                                                                                                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor power kW                              | 9 KW 220...230 V AC 50/60 Hz<br>18.5 KW 380...400 V AC 50/60 Hz<br>18.5 KW 415 V AC 50/60 Hz<br>18.5 KW 440 V AC 50/60 Hz<br>18.5 KW 500 V AC 50/60 Hz<br>18.5 KW 660...690 V AC 50/60 Hz                                                                                  |
| Maximum Horse Power Rating                  | 2 Hp 115 V at AC 50/60 Hz for 1 phase<br>5 Hp 230/240 V at AC 50/60 Hz for 1 phase<br>10 Hp 200/208 V at AC 50/60 Hz for 3 phase<br>10 Hp 230/240 V at AC 50/60 Hz for 3 phase<br>20 Hp 460/480 V at AC 50/60 Hz for 3 phase<br>25 hp 575/600 V at AC 50/60 Hz for 3 phase |
| Pole contact composition                    | 3 NO                                                                                                                                                                                                                                                                       |
| Control circuit type                        | AC 50/60 Hz                                                                                                                                                                                                                                                                |
| Auxiliary contact composition               | 1 NO                                                                                                                                                                                                                                                                       |
| [Uimp] rated impulse withstand voltage      | 6 kV IEC 60947                                                                                                                                                                                                                                                             |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                        |
| [Ith] conventional free air thermal current | 10 A 140 °F (60 °C) signalling circuit<br>50 A 140 °F (60 °C) power circuit                                                                                                                                                                                                |
| Irms rated making capacity                  | 140 A AC signalling circuit IEC 60947-5-1<br>250 A DC signalling circuit IEC 60947-5-1<br>550 A 440 V power circuit IEC 60947                                                                                                                                              |
| Rated breaking capacity                     | 550 A 440 V power circuit IEC 60947                                                                                                                                                                                                                                        |
| Associated fuse rating                      | 10 A gG signalling circuit IEC 60947-5-1<br>63 A gG <= 690 V type 1 power circuit<br>63 A gG <= 690 V type 2 power circuit                                                                                                                                                 |
| Average impedance                           | 2 mOhm - Ith 50 A 50 Hz power circuit                                                                                                                                                                                                                                      |
| [Ui] rated insulation voltage               | Power circuit 690 V IEC 60947-4-1<br>Power circuit 600 V CSA<br>Power circuit 600 V UL<br>Signalling circuit 690 V IEC 60947-1                                                                                                                                             |
| Electrical durability                       | 1 Mcycles 38 A AC-3 <= 440 V<br>0.6 Mcycles 52 A AC-1 <= 440 V                                                                                                                                                                                                             |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power dissipation per pole      | 2 W AC-3<br>5 W AC-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mounting Support                | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Connections - terminals         | Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end<br>Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end<br>Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible with cable end<br>Power circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible with cable end<br>Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end<br>Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible with cable end<br>Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible with cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end |
| Tightening torque               | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2<br>Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm<br>Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Operating time                  | 12...22 ms closing<br>4...19 ms opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Safety reliability level        | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Mechanical durability           | 10 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Maximum operating rate          | 3600 cyc/h 140 °F (60 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Coil technology                 | Without built-in suppressor module                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Control circuit voltage limits  | Drop-out 0.3...0.6 Uc 50/60 Hz 158 °F (70 °C))<br>Operational 0.8...1.1 Uc 50 Hz 140 °F (60 °C))<br>Operational 0.85...1.1 Uc 60 Hz 140 °F (60 °C))<br>Operational 1...1.1 Uc 50/60 Hz 158 °F (70 °C))                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Inrush power in VA              | 70 VA 60 Hz 0.75 68 °F (20 °C))<br>70 VA 50 Hz 0.75 68 °F (20 °C))                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Hold-in power consumption in VA | 7.5 VA 60 Hz 0.3 68 °F (20 °C))<br>7 VA 50 Hz 0.3 68 °F (20 °C))                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Auxiliary contacts type         | Mechanically linked 1 NO IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Signalling circuit frequency    | 25...400 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Minimum switching current       | 5 mA signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum switching voltage       | 17 V signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Insulation resistance           | > 10 MOhm signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Mechanical robustness           | Vibrations contactor open 2 Gn, 5...300 Hz)<br>Vibrations contactor closed 4 Gn, 5...300 Hz)<br>Shocks contactor open 10 Gn for 11 ms)<br>Shocks contactor closed 15 Gn for 11 ms)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Height                          | 3.35 in (85 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Width                           | 1.77 in (45 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Depth                           | 3.62 in (92 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Net Weight                      | 0.83 lb(US) (0.375 kg)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Non-overlap time                | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## Environment

|                                       |                                                                                                   |
|---------------------------------------|---------------------------------------------------------------------------------------------------|
| Standards                             | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 60947-4-1 |
| Product Certifications                | UL<br>CSA                                                                                         |
| Heat dissipation                      | 2...3 W 50/60 Hz                                                                                  |
| IP degree of protection               | IP20 front face IEC 60529                                                                         |
| Pollution degree                      | 3                                                                                                 |
| Protective treatment                  | TH IEC 60068-2-30                                                                                 |
| Ambient Air Temperature for Operation | -40...140 °F (-40...60 °C)                                                                        |
| Ambient Air Temperature for Storage   | -76...176 °F (-60...80 °C)                                                                        |
| Operating altitude                    | 0...6561.68 ft (0...2000 m)                                                                       |
| Flame retardance                      | V1 conforming to UL 94                                                                            |
| Fire resistance                       | 1562 °F (850 °C) IEC 60695-2-1                                                                    |

## Ordering and shipping details

|                       |                       |
|-----------------------|-----------------------|
| Category              | 22362-EASY TESYS DPE1 |
| Discount Schedule     | I13                   |
| GTIN                  | 3606481063267         |
| Nbr. of units in pkg. | 1                     |
| Package weight(Lbs)   | 14.11 oz (400.0 g)    |
| Returnability         | Yes                   |
| Country of origin     | ID                    |

## Packing Units

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 1       | PCE                       |
| Package 1 Height             | 3.98 in (10.1 cm)         |
| Package 1 width              | 1.77 in (4.5 cm)          |
| Package 1 Length             | 3.35 in (8.5 cm)          |
| Unit Type of Package 2       | S02                       |
| Number of Units in Package 2 | 16                        |
| Package 2 Weight             | 14.80 lb(US) (6.715 kg)   |
| Package 2 Height             | 5.91 in (15.0 cm)         |
| Package 2 width              | 11.81 in (30.0 cm)        |
| Package 2 Length             | 15.75 in (40.0 cm)        |
| Unit Type of Package 3       | P06                       |
| Number of Units in Package 3 | 256                       |
| Package 3 Weight             | 255.60 lb(US) (115.94 kg) |
| Package 3 Height             | 303.15 in (770.0 cm)      |
| Package 3 width              | 23.62 in (60.0 cm)        |
| Package 3 Length             | 31.50 in (80.0 cm)        |

## Offer Sustainability

|                           |                                                                                                                                                                                                                                                           |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status  | Green Premium product                                                                                                                                                                                                                                     |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| RECh Regulation           |  <a href="#">RECh Declaration</a>                                                                                                                                      |
| RECh free of SVHC         | Yes                                                                                                                                                                                                                                                       |
| EU RoHS Directive         | Compliant  <a href="#">EU RoHS Declaration</a>                                                                                                                         |
| Toxic heavy metal free    | Yes                                                                                                                                                                                                                                                       |

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Mercury free               | Yes                                           |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |