## **CT-ARE**



Products Low Voltage Products and Systems Control Products Electronic Relays and Controls Time Relays

General Information

Extended Product Type: CT-ARE

**Product ID:** 1SVR550127R1100 **EAN:** 4013614346354

Catalog Description: CT-ARE Time relay, true OFF-delay 1c/o, 0.1-10s, 24VAC/DC, 220-240VAC

Long Description: The CT-ARE is a single-function electronic time relay from the CT-E timer range. It provide

s an OFF-delay (true delay on break) function without auxiliary voltage and with a time ran ge from 0.1 s to 10 s. This time relay operates with a rated control supply voltage of 24 V A

C / DC / 220 - 240 V AC and has a 1 c/o (SPDT) output rated at 250 V / 4 A.

## Additional Information

Analog Inputs:	0
CB Certificate:	CB_DK-8575
CCC Certificate:	CCC_2010010303393101
Country of Origin:	Bulgaria (BG)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC111138D0201
Declaration of Conformity - CE:	1SVD981002-0001
EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
EAN:	4013614346354
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
EPLAN Function Definition:	Coil / Coil with special drive, 3 connection points / Coil, with drop-out delay, 3 connection points A1_A2_B1 Change-over contact / Change-over contact, 3 connection points / Change-over contact, off-delay 16_15_18
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
ETIM 6:	EC001439 - Timer relay
Environmental Information:	1SAA981011-2402
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SVC550000M9000
Invoice Description:	CT-ARE Time relay, true OFF-delay 1c/o, 0.1-10s, 24VAC/DC, 220-240VAC
Minimum Order Quantity:	1 piece
Mounting Position:	Any
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Digital Inputs:	0
Object Classification Code:	К
Output:	1 c/o (SPDT) contact
Package Level 1 EAN:	4013614346354
Package Level 1 Gross Weight:	0.081 kg
Package Level 1 Height:	83.1 mm
Package Level 1 Length:	24.6 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	84.2 mm
Power Loss:	Approximately 2 W

т голастинг турс.	OITANE
Product Name:	Time Relay
Product Net Depth:	78.5 mm
Product Net Height:	78 mm
Product Net Weight:	0.07 kg
Product Net Width:	22.5 mm
RMRS Certificate:	RMRS_1740021250
Rated Control Supply Voltage (U <sub>s</sub> ):	220 240 V AC 24 V AC/DC
Regulatory Compliance Mark (RCM):	Yes
RoHS Date:	1146
RoHS Information:	1SVD981002-0001
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CT-ARE Time relay, true OFF-delay
Standards:	EN 50581 IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14
Terminal Type:	Screw Terminals
Time Range:	0.1-10 s
Timer Relay Type:	True OFF-Delay
UL Certificate:	UL508_E140448
UNSPSC:	39121500
cUL Certificate:	cUL508_E140448
eClass:	7.0 27371790

