

A260-30-11 110V 50Hz / 110-120V 60Hz

[Print View..](#)
[Print to Pdf..](#)

General Information

Extended Product Type:	A260-30-11 110V 50Hz / 110-120V 60Hz
Product ID:	1SFL531001R8411
EAN:	7320500203354
Catalog Description:	A260-30-11 110V 50Hz / 110-120V 60Hz Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 690 V. Operated with control voltage, versions from 24....690 AC, 50 and 60 Hz



Categories

Products » Low Voltage Products and Systems » Control Products »
Contactors » Block Contactors

Ordering

EAN:	7320500203354
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	140.0 mm
Product Net Depth:	180.5 mm
Product Net Height:	227.0 mm
Product Net Weight:	5.750 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	200 mm
Package Level 1 Length:	220 mm
Package Level 1 Height:	280 mm
Package Level 1 Gross Weight:	5.75 kg
Package Level 1 EAN:	7320500203354

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 - 1.1 Uc) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 - 1.1 Uc) -40...+70 °C Close to Contactor for Storage -40...+70 °C
Maximum Operating Altitude Permissible:	3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Shock Direction: A 5 g Shock Direction: B1 5 g Shock Direction: B2 5 g Shock Direction: C1 5 g Shock Direction: C2 5 g
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Rated Operational Power AC-3 (P_e):	(220 / 230 / 240V) 80 kW (380 / 400V) 140 kW (415V) 140 kW (440V) 140 kW (500V) 180 kW (690V) 200 kW
Rated Operational Current AC-1 (I_e):	(690V) 40°C 400 A (690V) 55°C 350 A (690V) 70°C 290 A
Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Control Circuit Voltage (U_c):	50 Hz 110 V 60 Hz 110 ... 120 V
Terminal Type:	Screw Terminals
Coil Consumption:	Pull-in at Max Rated Control Circuit Voltage 50Hz 1350 V·A Pull-in at Max Rated Control Circuit Voltage 60Hz 1550 V·A Holding at Max Rated Control Circuit Voltage 60Hz 65 V·A Holding at Max Rated Control Circuit Voltage 50Hz 60 V·A

Technical UL/CSA

Maximum Operating Voltage UL/CSA: Main Circuit 600 V

Certificates and Declarations (Document Number)

BV Certificate:	09826/C0 BV
CCC Certificate:	CQC_2008010304279325
Declaration of Conformity - CE:	1SFA1-45
DNV Certificate:	DNV_E-12191
GL Certificate:	GL_15529-00HH
LOVAG Certificate:	IT00047 IT99056 IT99056 SE-0003004
LR Certificate:	LR_12-70003
RINA Certificate:	ELE060313XG/001
RMRS Certificate:	RMRS_12-03683-315
RoHS Information:	1SFC101046D0203

Classifications

E-nummer:	3227883
UNSPSC:	39121529
