

# ABB430C9W



Ind. P&S#ABB430C9W



## General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | ABB430C9W   |
| Product ID            | 2CMA100335R1000   |
| EAN                   | 7392696003353   |
| Catalog Description   | Ind. P&S#ABB430C9W  |
| Long Description      | IEC Connector 30A 3P4W 3phase 250V Clock Position Of Grounding Contact 9 hour Color code Blue |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696003353       |
| Minimum Order Quantity | 1 piece             |
| Country of Origin      | Czech Republic (CZ) |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 92 mm   |
| Product Net Height         | 102 mm  |
| Product Net Length         | 195 mm  |
| Product Net Depth / Length | 195 mm  |
| Product Net Weight         | 0.26 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 114 mm        |
| Package Level 1 Depth / Length | 114 mm        |
| Package Level 1 Height         | 230 mm        |
| Package Level 1 Gross Weight   | 0.26 kg       |
| Package Level 1 EAN            | 7392696003353 |
| Package Level 1 Units          | 1 piece       |
| Package Level 2 Units          | 171 piece     |

## Technical UL/CSA

|                      |      |
|----------------------|------|
| Ampere Rating UL/CSA | 30 A |
|----------------------|------|

## Certificates and Declarations (Document Number)

|                                |                              |
|--------------------------------|------------------------------|
| Declaration of Conformity - CE | 2CMC700005D0020              |
| Declaration                    | 2CMC700005D0020              |
| Environmental Information      | 2CMC000056M0000              |
| RoHS Information               | 2CMC700005D0020              |
| UL Certificate                 | E163435-19950105-UL_cert_C_R |

## Additional Information

|                                 |  |
|---------------------------------|--|
| Additional Information          | 3P+E                                   |
| Cable Cross-Section             | 2.5 ... 6 mm <sup>2</sup>              |
| Color                           | Blue                                   |
| Connection Type                 | Screw clamp                            |
| Degree of Protection            | IP67<br>IP69                           |
| Enclosure Material              | Thermoplastic polyester (PBT)          |
| Frequency (f)                   | 50 Hz<br>60 Hz                         |
| Function                        | Connector                              |
| Housing Material                | Thermoplastic (PBT)                    |
| Invoice Description             | Ind. P&S#ABB430C9W                     |
| Number of Poles                 | 4                                      |
| Order Multiple                  | 1 piece                                |
| Product Main Type               | TC                                     |
| Product Name                    | Industrial connector                   |
| Protection Type                 | Watertight                             |
| Rated Current (I <sub>n</sub> ) | 30 A                                   |
| Rated Voltage (U <sub>r</sub> ) | 200 ... 250 V                          |
| Recommended Screw Driver        | PH2                                    |
| RoHS Date                       | L23                                    |
| Standards                       | UL 1682, 1686 / CSA C22.2 No. 182.1-13 |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

