

ABB520C7W



Ind. P&S#ABB520C7W

General Information

| | |
|-----------------------|--|
| Extended Product Type | ABB520C7W |
| Product ID | 2CMA100323R1000 |
| EAN | 7392696003230 |
| Catalog Description | Ind. P&S#ABB520C7W |
| Long Description | IEC Connector 20A 4P5W 3phase-Y 277/480V Clock Position Of Grounding Contact 7 hour Color code Red |

Ordering

| | |
|------------------------|---------------------|
| EAN | 7392696003230 |
| Minimum Order Quantity | 1 piece |
| Country of Origin | Czech Republic (CZ) |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 86 mm |
| Product Net Height | 97 mm |
| Product Net Length | 195 mm |
| Product Net Depth / Length | 195 mm |
| Product Net Weight | 0.23 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 135 mm |
| Package Level 1 Depth / Length | 140 mm |
| Package Level 1 Height | 200 mm |
| Package Level 1 Gross Weight | 0.23 kg |
| Package Level 1 EAN | 7392696003230 |
| Package Level 1 Units | 1 piece |
| Package Level 2 Units | 174 piece |

Technical UL/CSA

| | |
|----------------------|------|
| Ampere Rating UL/CSA | 20 A |
|----------------------|------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|------------------------------|
| Declaration of Conformity - CE | 2CMC700005D0020 |
| Declaration | 2CMC700005D0020 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0020 |
| UL Certificate | E163435-19950105-UL_cert_C_R |

Additional Information

| | |
|---------------------------------|--|
| Additional Information | 3P+N+E |
| Cable Cross-Section | 1 ... 2.5 mm ² |
| Color | Red |
| Connection Type | Screw clamp |
| Degree of Protection | IP67 IP69 |
| Enclosure Material | Thermoplastic polyester (PBT) |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Connector |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#ABB520C7W |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | TC |
| Product Name | Industrial connector |
| Protection Type | Watertight |
| Rated Current (I _n) | 20 A |
| Rated Voltage (U _r) | 277/480 V |
| Recommended Screw Driver | PH2 |
| RoHS Date | L23 |
| Standards | UL 1682, 1686 / CSA C22.2 No. 182.1-13 |

Classifications

| | |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

