

Catalog Number: AE9-30-11-81
UPC Number: 66201976372
Status: A

AE9 3P CONTR,24VDC

North American Specifications (UNSPSC)

UNSPSC	39121529 Contactors
IGCC	4755 Contactors
Brand Name	ABB
Special Features	Features: AE types: With laminated magnetic circuit and double-winding coil fed from DC supply via a CDL5 insertion contact mounted on the device The CDL5 has an NC lagging contact for insertion of the second winding; Number Of Poles: 3; Wire Size: Main Conductors: Rigid: (1) 1 - 4 SQ-MM Solid, (2) 1 - 4 SQ-MM Stranded, Flexible: (1 Or 2) 0.75 - 2.5 SQ-MM, Auxiliary Conductors: Rigid: (1) 1 - 4 SQ-MM, (2) 1 - 4 SQ-MM, Flexible: (1 Or 2) 0.75 - 2.5 SQ-MM; Operating Current: 30 AMP; Maximum Breaking Capacity: 90 AMP At 690 V, 250 AMP At 440 V; Motor Rating: 2 HP At 208 V, 2 HP At 240 V, 5 HP At 480 V, 7.5 HP At 575/600 V
Standard	UL Listed, IEC 947-4-1, EN 50005, EN 50012 And NEMA Standards

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	0.91 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com