

AF63-30-11 100-250V 50Hz / 100-250V 60Hz / 100-250V DC

[Print View..](#)
[Print to Pdf..](#)

General Information

Extended Product Type:	AF63-30-11 100-250V 50Hz / 100-250V 60Hz / 100-250V DC
Product ID:	1SBL377001R7011
EAN:	3471522115003
Catalog Description:	AF63-30-11 100-250V 50Hz / 100-250V 60Hz / 100-250V DC Contactor
Long Description:	<p>AF63 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC and 220 V DC. The contactors can also be used for many other applications such as bypass, capacitor switching, lighting, DC power circuits... The AF... contactors are fitted with an electronic coil interface which accepts a wide control voltage range, on AC 50/60 Hz or DC supplies. The same contactor can accept various supply voltages according to the different countries where the electrical equipment will be installed, or some fluctuation in the control voltage due to the local supply or network. The AF... contactors are also fully suitable for operation in AC or DC control circuit liable to voltage interruptions or voltage dip risks. Advantages: - Wide voltage range, e.g. 100 ... 250 V AC and DC - Can manage large voltage variations - Reduced power consumption - Very distinct closing and opening - Noise free - Can withstand voltage interruptions or voltage dips in the control supply (≤ 20 ms). The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles and 2 built-in auxiliary contacts, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.</p>



Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

Ordering

EAN:	3471522115003
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	82.0 mm
Product Net Depth:	108.0 mm
Product Net Height:	110.0 mm
Product Net Weight:	1.220 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	140 mm
Package Level 1 Length:	146 mm
Package Level 1 Height:	96 mm
Package Level 1 Gross Weight:	1.22000 kg
Package Level 1 EAN:	3471522115003
Package Level 2 Units:	20 piece

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C Close to Contactor for Storage -60 ... +80 °C Close to Contactor without Thermal O/L Relay -40 ... +70 °C
Maximum Operating Altitude Permissible:	3000 m
RoHS Status:	No declaration needed

Technical

Rated Operational Power AC-3 (P_e):	(220 / 230 / 240V) 18.5 kW (380 / 400V) 30 kW (415V) 37 kW (440V) 37 kW (500V) 37 kW (690V) 37 kW
Rated Operational Current AC-1 (I_e):	(690V) 40°C 115 A (690V) 55°C 95 A (690V) 70°C 80 A
Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Terminal Type:	Screw Terminals
Coil Consumption:	Pull-in at Max Rated Control Circuit Voltage 50Hz 210 V·A Pull-in at Max Rated Control Circuit Voltage 60Hz 210 V·A Holding at Max Rated Control Circuit Voltage 60Hz 7 V·A Holding at Max Rated Control Circuit Voltage 60Hz 2.8 W Holding at Max Rated Control Circuit Voltage 50Hz 7 V·A Holding at Max Rated Control Circuit Voltage 50Hz 2.8 W

Certificates and Declarations (Document Number)

CCC Certificate:	CCC_2008010304269002
Declaration of Conformity - CE:	1SBD250858C1000
EAC Certificate:	EAC_RU C-FR ME77 B01010
GOST Certificate:	GOST_POCCFRME77B07175
RoHS Information:	1SBC101059D0201
