

# EOT16U3S4-P



Products → Low Voltage Products and Systems → Enclosed Switches → Enclosed Disconnect Switches

## General Information

<b>Extended Product Type:</b>	EOT16U3S4-P
<b>Product ID:</b>	1SCA022823R7610
<b>EAN:</b>	6417019282299
<b>Catalog Description:</b>	EOT16U3S4-P Enclosed Disconnect Switch
<b>Long Description:</b>	Enclosed Switch Disconnecter, 3-p. Max. Horse power rating at three phase 480V 10HP. General purpose current rating 16A. Stainless steel enclosure, NEMA Type 4/4X Watertight, Pistol handle. Interlocked cover. Defeatable interlocking.

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85371098

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SXU301074B0201
---	-----------------

## Dimensions

<b>Product Net Width:</b>	134.1 mm 5.28 in
<b>Product Net Height:</b>	215.9 mm 8.5 in
<b>Product Net Depth:</b>	83.3 mm 3.28 in
<b>Product Net Weight:</b>	2.1 kg 4.63 lb

## Technical

<b>Rated Operational Current AC-22A (<math>I_e</math>):</b>	(380 ... 415 V) 16 A (690 V) 16 A
<b>Rated Operational Current AC-23A (<math>I_e</math>):</b>	(690 V) 16 A (690 V) 380415V10 A
<b>Conventional Thermal Current (<math>I_{the}</math>):</b>	7.5 A
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	acc. to IEC/EN 60664-1 750 V
<b>Rated Operational Voltage:</b>	Main Circuit 750 V
<b>Pollution Degree:</b>	3
<b>Handle Color:</b>	Black
<b>Handle Type:</b>	Pistol handle
<b>Switches Operating Mechanism:</b>	On the Front of the Switch
<b>Position of Line Terminals:</b>	Top In - Bottom Out
<b>Number of Poles:</b>	3
<b>Cable Cross-Section:</b>	10 mm <sup>2</sup>
<b>Cable Entry Position:</b>	Up/Down
<b>Cable Outlets Per Side:</b>	Blank / Blank
<b>Degree of Protection:</b>	acc. to IEC 60529 IP65
<b>Enclosure Material:</b>	Stainless steel
<b>Mounted Auxiliary Contacts:</b>	0 NO, 0 NC
<b>Terminal Type:</b>	Screw Terminals
<b>Tightening Torque:</b>	acc. IEC 60947-1 0.8 N·m

## Technical Data

<b>Maximum Operating Voltage UL/CSA:</b>	600 V
<b>Horsepower Rating UL/CSA:</b>	(220 ... 240 V AC) Three Phase 5 Hp (480 V AC) 10 Hp (600 V AC) 10 Hp
<b>Ampere Rating UL/CSA:</b>	16 A
<b>Tightening Torque UL/CSA:</b>	Main Circuit 7 in·lb

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	0
<b>Instructions and Manuals:</b>	1SCC340019M0202

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	142 mm 5.59 in
<b>Package Level 1 Length:</b>	165 mm 6.5 in
<b>Package Level 1 Height:</b>	227 mm 8.94 in
<b>Package Level 1 Gross Weight:</b>	2.1 kg 4.63 lb
<b>Package Level 1 EAN:</b>	6417019282299

## Classifications

<b>Object Classification Code:</b>	Q
<b>ETIM 5:</b>	EC000216 - Switch disconnecter
<b>ETIM 6:</b>	EC000216 - Switch disconnecter

