EOT32U3M1-P



Products + Low Voltage Products and Systems + Enclosed Switches + Enclosed Disconnect Switches

General Information

Extended Product Type: EOT32U3M1-P

Product ID: 1SCA022823R7010

EAN: 6417019282237

Catalog Description: EOT32U3M1-P Enclosed Disconnect Switch

Long Description: Enclosed Switch Disconnector, 3-p. Max. Horse power rating at three phas

e 480V 20HP. General purpose current rating 40A. Steel sheet enclosure, NEMA Type 1 Indoor, Pistol handle. Interlocked cover. Defeatable interlock

ing.

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85371098

Popular Downloads

Data Sheet, Technical Information: 1SXU301074B0201

Instructions and Manuals: 1SCC340019M0202

Dimensions

Product Net Width: 134.1 mm

5.28 in

Product Net Height: 215.9 mm

8.5 in

Product Net Depth / Length: 83.3 mm

3.28 in

Product Net Weight: 2.1 kg

4.63 lb

Technical

Conventional Thermal Current Fu

Fully Enclosed 11 A

(I_{the}):

Rated Insulation Voltage (Ui): acc. to IEC/EN 60664-1 750 V

Pollution Degree: 3

Handle Color: Black

Handle Type: Pistol handle

Switches Operating Mechanism: On the Front of the Switch

Position of Line Terminals: Top In - Bottom Out

Number of Poles: 3

Cable Cross-Section:	10 mm²
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2x(ø1 / 25.4+ø0.75 / 19.1)
Degree of Protection:	acc. to IEC 60529 IP30
Enclosure Material:	Steel sheet
Mounted Auxiliary Contacts:	0 NO, 0 NC
Terminal Type:	Screw Terminals

Technical UL/CSA

Maximum Operating Voltage

600 V

UL/CSA:

Horsepower Rating UL/CSA: (220 ... 240 V AC) Three Phase 10 Hp

(480 V AC) 20 Hp (600 V AC) 25 Hp

Ampere Rating UL/CSA: 40 A

Tightening Torque UL/CSA: Main Circuit 7 in·lb

Certificates and Declarations (Document Number)

Instructions and Manuals: 1SCC340019M0202

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	142 mm
	5.59 in
Package Level 1 Depth / Length:	165 mm
	6.5 in
Package Level 1 Height:	227 mm
	8.94 in
Package Level 1 Gross Weight:	2.1 kg
	4.63 lb
Package Level 1 EAN:	6417019282237

Classifications

Object Classification Code:	Q
ETIM 5:	EC000216 - Switch disconnector
ETIM 6:	EC000216 - Switch disconnector
ETIM 7:	EC000216 - Switch disconnector

