# EOT32U3P4-1P1



Products + Low Voltage Products and Systems + Enclosed Switches + Enclosed Disconnect Switches

General Information

 Extended Product Type:
 EOT32U3P4-1P1

 Product ID:
 1SCA104266R1001

 EAN:
 6417019384733

Catalog Description: EOT32U3P4-1P1 Enclosed Disconnect Switch

Long Description: Enclosed Switch Disconnector, 3-p. Max. Horse power rating at three phas

e 480V 20HP. General purpose current rating 40A. Plastic enclosure, NEM A Type 4/4X Watertight, Pistol handle. Interlocked cover. Defeatable interlo

cking.

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85371098

Popular Downloads

Data Sheet, Technical Information: 1SXU301074B0201

Instructions and Manuals: 1SCC340019M0202

**Dimensions** 

Product Net Width: 100 mm

3.94 in

Product Net Height: 161.4 mm

6.35 in

Product Net Depth / Length: 81 mm

3.19 in

Product Net Weight: 0.66 kg

1.46 lb

**Technical** 

Rated Operational Current AC-22A (380 ... 415 V) 40 A

<sub>e</sub>): (690 V) 40 A

Rated Operational Current AC-23A (690 V) 23 A

(I<sub>e</sub>): (690 V) 380415V12 A

Conventional Thermal Current 11 A

(I<sub>the</sub>):

Rated Insulation Voltage (U<sub>i</sub>): acc. to IEC/EN 60664-1 750 V

Rated Operational Voltage: Main Circuit 750 V

Pollution Degree: 3

Handle Color:	Red / Yellow
Handle Type:	Pistol handle
Switches Operating Mechanism:	On the Front of the Switch
Position of Line Terminals:	Top In - Bottom Out
Number of Poles:	3
Cable Cross-Section:	10 mm²
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2x(ø1 / 25.4+ø0.75 / 19.1)
Degree of Protection:	acc. to IEC 60529 IP65
Enclosure Material:	Plastic
Mounted Auxiliary Contacts:	1 NO, 0 NC
Terminal Type:	Screw Terminals
Tightening Torque:	acc. IEC 60947-1 0.8 N·m

## Technical UL/CSA

**Maximum Operating Voltage** 

UL/CSA:

600 V

Horsepower Rating UL/CSA: (220 ... 240 V AC) Three Phase 10 Hp

(480 V AC) 20 Hp (600 V AC) 25 Hp

Ampere Rating UL/CSA: 40 A

Tightening Torque UL/CSA: Main Circuit 7 in·lb

# Certificates and Declarations (Document Number)

Declaration of Conformity - CE: (

Instructions and Manuals: 1SCC340019M0202

#### **Container Information**

Package Level 1 Units:	1 piece
Package Level 1 Width:	135 mm
	5.31 in
Package Level 1 Depth / Length:	112 mm
	4.41 in
Package Level 1 Height:	172 mm
	6.77 in
Package Level 1 Gross Weight:	0.66 kg
	1.46 lb
Package Level 1 EAN:	6417019384733

## Classifications

Object Classification Code: Q

ETIM 5:	EC000216 - Switch disconnector
ETIM 6:	EC000216 - Switch disconnector
ETIM 7:	EC000216 - Switch disconnector

