

F202 A-25/0,03 AP-R



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs
Residual Current Devices RCDs

General Information

Extended Product Type: F202 A-25/0,03 AP-R

Product ID: 2CSF202401R1250

EAN: 8012542785101

Catalog Description: F202 A-25/0,03 AP-R Res. Current Dev.

Long Description: The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product provides the best compromise between safety and continuity in the service, thanks to the resistance to unwanted trippings.

Additional Information

Country of Origin:	Italy (IT)
Customs Tariff Number:	85363030
Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	9AKK106713A5602
E-number:	2160175
EAN:	8012542785101
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Ground fault current circuit breaker
EPLAN Function Definition:	Ground fault current circuit-breaker / Ground fault current circuit breakers, 4 connection points / Ground fault current circuit breaker, two-pole 1/2 2/1 3/4 4/3
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6:	EC000003 - Residual current circuit breaker (RCCB)
Environmental Information:	S-P-00080
Instructions and Manuals:	2CSF423001D6406
Invoice Description:	F202 A-25/0,03 AP-R Res. Current Dev.
Maximum Operating Voltage UL/CSA:	277 V AC
Minimum Order Quantity:	1 piece
Number of Poles:	2
Object Classification Code:	Q
Operating Characteristic:	Instantaneous (APR High Immunity)
Options Provided:	-
Package Level 1 EAN:	8012542785101
Package Level 1 Gross Weight:	0.225 kg
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.041 m
Power Loss:	at Rated Operating Conditions per Pole 1 W
Product Main Type:	F200
Product Name:	Residual Current Circuit Breaker
Product Net Depth:	0.069 m
Product Net Height:	0.085 m
Product Net Weight:	0.200 kg
Product Net Width:	0.035 m
Rated Current (I_n):	25 A
Rated Frequency (f):	50 ... 60 Hz
Rated Operational Voltage:	230 V AC
Rated Residual Current:	30 mA
Rated Voltage (U_r):	230/400 V
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	Residual Current Device F202 A-25/0,03 AP-R
Standards:	IEC/EN 61008 UL 1053
Type of Residual Current:	A type
Accessories Available:	Yes

