F202 AC-40/0,1 IEC



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs Residual Current Devices RCDs

General Information	
Extended Product Type:	F202 AC-40/0,1 IEC
Product ID:	2CSF202005R2400
EAN:	8012542815105
Catalog Description:	F202 AC-40/0,1 IEC - Resid. Current Dev.
Long Description:	The RCCBs F200 series assures protection to people and installations against fault curren t to earth. This product is manufactured according to international IEC standards, for the m arkets where it is required.

Additional Information

Country of Origin:	Italy (IT)
Customs Tariff Number:	85363030
Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	9AKK106713A5602
EAN:	8012542815105
ЕПМ 4:	EC000003 - Residual current circuit breaker (RCCB)
ЕПМ 5:	EC000003 - Residual current circuit breaker (RCCB)
ЕТІМ 6:	EC000003 - Residual current circuit breaker (RCCB)
Environmental Information:	S-P-00080
Instructions and Manuals:	2CSF423001D6406
Invoice Description:	F202 AC-40/0,1 IEC - Resid. Current Dev.
Maximum Operating Voltage UL/CSA:	277 V AC
Minimum Order Quantity:	1 piece
Number of Poles:	2
Object Classification Code:	Q
Operating Characteristic:	Instantaneous
Options Provided:	-
Package Level 1 EAN:	8012542815105
Package Level 1 Gross Weight:	0.225 kg
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.041 m
Power Loss:	at Rated Operating Conditions per Pole 2.4 W
Product Main Type:	F200
Product Name:	Residual Current Circuit Breaker
Product Net Depth:	0.069 m
Product Net Height:	0.085 m
Product Net Weight:	0.200 kg
Product Net Width:	0.035 m
Rated Current (I _n):	40 A
Rated Frequency (f):	50 60 Hz
Rated Operational Voltage:	230 V AC
Rated Residual Current:	100 mA
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	Residual Current Device - F202 AC-40/0,1 IEC
Standards:	IEC 61008
Type of Residual Current:	AC type
Accessories Available:	Yes

