F204 AC-100/0,3 IEC



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs Residual Current Devices RCDs

General Information

 Extended Product Type:
 F204 AC-100/0,3 IEC

 Product ID:
 2CSF204005R3900

 EAN:
 8012542937203

Catalog Description: F204 AC-100/0,3 IEC - Resid. Curr. Dev.

Long Description: The RCCBs F200 series assures protection to people and installations against fault curren

t to earth. This product is manufactured according to international IEC standards, for the m

arkets where it is required.

Additional Information

Country of Origin:	ltaly (IT)
Customs Tariff Number:	85363030
Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	9AKK106713A5602
EAN:	8012542937203
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ЕПМ 5:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6:	EC000003 - Residual current circuit breaker (RCCB)
Environmental Information:	S-P-00081
Instructions and Manuals:	2CSF423001D6406
Invoice Description:	F204 AC-100/0,3 IEC - Resid. Curr. Dev.
Minimum Order Quantity:	1 piece
Number of Poles:	4
Object Classification Code:	Q
Operating Characteristic:	Instantaneous
Options Provided:	-
Package Level 1 EAN:	8012542937203
Package Level 1 Gross Weight:	0.403 kg
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.082 m
Position of Neutral Terminals:	Right
Power Loss:	at Rated Operating Conditions per Pole 8.2 W
Product Main Type:	F200
Product Name:	Residual Current Circuit Breaker
Product Net Depth:	0.069 m
Product Net Height:	0.085 m
Product Net Weight:	0.360 kg
Product Net Width:	0.070 m
Rated Current (I _n):	100 A
Rated Frequency (f):	50 60 Hz
Rated Operational Voltage:	230 / 400 V AC
Rated Residual Current:	300 mA
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	Residual Current Device - F204 AC-100/0,3 IEC
Standards:	IEC 61008
Type of Residual Current:	AC type
Accessories Available:	Yes

