HKF1-11



Products Low Voltage Pro	oducts and Systems Control Products Manual Motor Starters Manual Motor Starters Accessories
Parts & Services Drives	Medium voltage AC drives Industrial drives ACS2000
Parts & Services Drives	Medium voltage AC drives Special purpose drives ACS1000
Parts & Services Drives	Medium voltage AC drives Special purpose drives ACS5000
Parts & Services Drives	Medium voltage AC drives Special purpose drives ACS6000
General Information	
Extended Product Type:	HKF1-11
Product ID:	1SAM201901R1001
EAN:	4013614320354
Catalog Description:	HKF1-11 Auxiliary Contact
Long Description:	HKF1-11 Aux-contact for frontmounting
Additional Information	
ABS Certificate:	1SAA963001-0101
Accessory Type: Ambient Air Temperature:	Auxiliary Contact Operation -20 +55 °C
	Storage -50 +80 °C
BV Certificate:	1SAA963000-0204
CB Certificate:	1SAA963003-2001
CCC Certificate:	1SAA918002-3802
Connecting Capacity Auxiliar UL/CSA:	ry Circuit Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG
Connecting Capacity Auxiliar	ry Circuit: Flexible with Ferrule 1/2x 0.75 1.5 mm² Flexible with Insulated Ferrule 1/2x 0.75 1.5 mm² Flexible 1/2x 0.75 1.5 mm² Rigid 1/2x 1.0 2.5 mm²
Contact Rating UL/CSA:	B300 R300
Core Credit:	0.00
Core Credit: Country of Origin:	0.00 Bulgaria (BG)
Country of Origin: Customs Tariff Number: DNV Certificate:	Bulgaria (BG) 85365080 1SAA963001-0303
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02
Country of Origin: Customs Tariff Number: DNV Certificate:	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 ISAD938501-0191 1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938504-0183 1SAD938502-0190
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 ISAD938501-0191 1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938502-0183 1SAD938502-0190 1SAD938510-0125
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 ISAD938501-0191 1SAD938516-0060 1SAD938516-0060 1SAD938502-0188 1SAD938502-0183 1SAD938502-0190 1SAD938510-0125 3112001
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C E-nummer: EAC Certificate:	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 ISAD938501-0191 1SAD938501-0191 1SAD938502-0181 1SAD938502-0188 1SAD938502-0180 1SAD938502-0190 1SAD938510-0125 3112001 1SAA963000-2701
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C E-nummer: EAC Certificate: EAN:	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938502-0188 1SAD938502-0190 1SAD938502-0190 1SAD938510-0125 3112001 1SAA963000-2701 4013614320354
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C E-nummer: EAC Certificate: EAN: EPLAN Catalog Tree:	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 1SAD938501-0191 1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938504-0183 1SAD938502-0190 1SAD938510-0125 3112001 4013614320354 Electrical engineering / Protection devices / Motor overload switch
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C E-nummer: EAC Certificate: EAN: EPLAN Catalog Tree: ETIM 4:	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 1SAD938501-0191 1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938502-0188 1SAD938502-0188 1SAD938502-0190 1SAD938510-0125 3112001 1SAA963000-2701 4013614320354 Electrical engineering / Protection devices / Motor overload switch EC002498 - Accessories for low-voltage switch technology
Country of Origin: Customs Tariff Number: DNV Certificate: Data Sheet, Technical Inform Declaration of Conformity - C E-nummer: EAC Certificate: EAN: EPLAN Catalog Tree: ETIM 4: ETIM 5:	Bulgaria (BG) 85365080 1SAA963001-0303 nation: 1SBC100192C02 ISAD938501-0191 1SAD938502-0188 1SAD938502-0188 1SAD938502-0188 1SAD938502-0190 1SAD938510-0125 3112001 1SAA963000-2701 4013614320354 Electrical engineering / Protection devices / Motor overload switch EC002498 - Accessories for low-voltage switch technology EC002498 - Accessories for low-voltage switch technology

IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC131011M6802
	2CDC131034M6801 2CDC131022M6802
Invoice Description:	HKF1-11 Aux-contact for frontmounting
LR Certificate:	1SAA963001-0501
	1SAA963001-0502
	1SAA963000-0505
Maximum Operating Voltage UL/CSA:	Main Circuit 250 V AC
Minimum Order Quantity:	1 piece
Mounting Position:	Position 1 to 6
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Object Classification Code:	Q
Package Level 1 EAN:	4013614481413
Package Level 1 Gross Weight:	0.195 kg
Package Level 1 Height:	50 mm
Package Level 1 Length:	36 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	148 mm
Package Level 2 EAN:	4013614522727
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Width:	280 mm
Part Type:	New
Part Type: Product Main Type:	New HKF1
Product Main Type:	HKF1
Product Main Type: Product Name:	HKF1 Auxiliary Contact
Product Main Type: Product Name: Product Net Depth:	HKF1 Auxiliary Contact 26.5 mm
Product Main Type: Product Name: Product Net Depth: Product Net Height:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (240 V) 6 A (380 / 400 V) 3 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0 A (600 V) 0 A
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Inpulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Inpulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{mp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e): Rated Operational Voltage: Recommended Screw Driver:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e): Rated Operational Voltage: Recommended Screw Driver: RoHS Date:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V M3 Pozidriv 2 0276
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Inpulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e): Rated Operational Voltage: Recommended Screw Driver: RoHS Date: RoHS Information:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0 A (600 V) 0 A (250 V 250 V 138A963001-4407

Short Description:	HKF1-11 Auxcontact for frontmounting
Standards:	IEC/EN 60947-1
	IEC/EN 60947-4-1
	IEC/EN 60947-5-1
	UL 60947-1
	UL 60947-4-1
Suitable For:	MS116
	MS132
	MO132
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Auxiliary Circuit 0.8 1.2 N·m
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in Ib
UL Certificate:	UL_E137861
UNSPSC:	39121500
Wire Stripping Length:	Auxiliary Circuit 8 mm
cUL Certificate:	cUL_E137861
eClass:	7.0 27379201
/here Used (as a spare part for	r "Products")

Where Used (as a spare part for "Products")

4 Products

ldentifier	Description	Qty	Unit Of Measure
ACS 1000	No Description Available	1	piece
ACS 2000	No Description Available	1	piece
ACS 5000 Water Cooled	No Description Available	1	piece
ACS 6000	No Description Available	1	piece

Filter

Product specific part data

Filter **4 Products** Product Category **Drive Part Category** ACS 2000 ACS2000 Switches, Relays, Contactors ACS 1000 ACS1000 Switches, Relays, Contactors ACS5000 ACS 5000 Water Cooled Switches, Relays, Contactors ACS 6000 ACS6000 Switches, Relays, Contactors

