




KT

Grommets, small, single



1

Product Description

Cable grommets KT small are used with the following cable entry frames:

KEL-U/KEL-ER/KEL-FG/KEL (8 - 36) | KVT (38 - 42)

The model range KT small is designed for cable diameters from 1 to 17 mm.

Assembly Note

When installing the grommets, the flat side should be facing the middle of the frame. This allows the flat sides of adjacent grommets to match up and provide a secure seal.

Specifications KT gray

Material	Elastomer
Flame class	UL94-Vo
IP rating	KT round, single: up to IP65 (in combination with KEL-ER frame) KT special/blank: IP54
NEMA type rating	up to NEMA type 4X (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free

Specifications KT black

Material	Elastomer
Flame class	UL94-HB
IP rating	KT round, single: up to IP65 (in combination with KEL-ER frame) KT special/blank: IP54
NEMA type rating	up to NEMA type 4X (acc. to UL 50E)
Temperature	- 30°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Higher chemical resistance

Accessories

ST Plugs 49

Description	Type	Order No gray	Order No black	Clamping range	PU
BTK		41251	41351	Blank grommet	10
KT 1	NEW	39941	39943	1 - 2 mm	10
KT 2		39934	41302	2 - 3 mm	10
KT 3		41203	41303	3 - 4 mm	10
KT 4		41204	41304	4 - 5 mm	10
KT 5		41205	41305	5 - 6 mm	10
KT 6		41206	41306	6 - 7 mm	10
KT 7		41207	41307	7 - 8 mm	10
KT 8		41208	41308	8 - 9 mm	10
KT 9		41209	41309	9 - 10 mm	10
KT 10		41210	41310	10 - 11 mm	10
KT 11		41211	41311	11 - 12 mm	10
KT 12		41212	41312	12 - 13 mm	10
KT 13		41213	41313	13 - 14 mm	10
KT 14		41214	41314	14 - 15 mm	10
KT 15		41215	41315	15 - 16 mm	10
KTs 16		39901	39912	16 mm	10
KTs 17		39900	39913	17 mm	10
KT oval		39930	-	approx. 8 x 4 mm	10
KT S1		39931	-		10
KT tele		39929	-	Telephone cable	10
KT tele1		41257	-	Data cable RJ12	10
KT tele2		41258	-	Data cable RJ10 / RJ45	10

*Only valid for gray product types






KT

Grommets, small, multi



1

Type	Order No gray	Order No black	Clamping range	PU	Description
KT 2 1 NEW	39942	39944	2× Ø 1 mm	10	 KT 2 x
KT 2 2	39935	39936	2× Ø 2 mm	10	
KT 2 3	39939	39940	2× Ø 3 mm	10	
KT 2 4	39906	39907	2× Ø 4 mm	10	
KT 2 5	41200	39904	2× Ø 5 mm	10	
KT 2 6	41201	39905	2× Ø 6 mm	10	
KT 2 7	41202	39916	2× Ø 7 mm	10	
KT 2 8	39917	39918	2× Ø 8 mm	10	
KT 4 2	39937	39938	4× Ø 2 mm	10	 KT 4 x
KT 4 3	39914	39915	4× Ø 3 mm	10	
KT 4 4	39909	39911	4× Ø 4 mm	10	
KT 4 5	39908	39910	4× Ø 5 mm	10	
KT 4 6	39932	39933	4× Ø 6 mm	10	
KT ASI	39902	39903	1 ASI-cable	10	
KT-ASI2 rl	39922	39924	2 ASI-cables	10	
KT-ASI2 ll	39921	39923	2 ASI-cables	10	 KT ASI2 ll

Product Description

Cable grommets KT small are used with the following cable entry frames:

KEL-U/KEL-ER/KEL (8 - 34) | KVT (38 - 42)

The model range KT small is designed for cable diameters from 1 to 17 mm.

Assembly Note

When installing the grommets, the flat side should be facing the middle of the frame. This allows the flat sides of adjacent grommets to match up and provide a secure seal.

Specifications KT gray

Material	Elastomer
Flame class	UL94-Vo
IP rating	KT round, multi: IP54 KT special, multi: IP54
NEMA type rating	NEMA type 12 (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free

Specifications KT black

Material	Elastomer
Flame class	UL94-HB
IP rating	KT round, multi: IP54 KT special, multi: IP54
NEMA type rating	NEMA type 12 (acc. to UL 50E)
Temperature	- 30°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Higher chemical resistance

Accessories

ST Plugs 49

*Only valid for gray product types