



Interface and Converter Products T&B Catalog Number:

UPC Number: Status: Description: 1SVR405611R1100 66201936264 Active

Plugin control relay with 24 VDC rated control supply voltage, DPDT (2 c/ o) contacts, contacts, with LED indicator and 250 V, 12 A contact rating **Application**

	For applications where low current control voltage is used to switch higher current or voltage loads
	Used with PLC, Microcontrollers, Fieldbus con- trollers and PC to control power loads
General	
Series	CR-M
Output Contacts	DPDT
Operation-Function	Control Relay
Dimension Information	
L x W x D (inches) Specifications	1.08 x 0.83 x 1.40
opooliteatione	
Input Voltage (DC)	24
Rated Output Voltage (VDC)	250
Supply Voltage (DC)	24
LED Indicator	1
Packaging	
T&B Order Multiple	10
T&B Inner Pack	1
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	7.5 lbs. per 100
Certifications	
Approvals	UL

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com