



Interface and Converter Products

T&B Catalog Number:

1SVR405622R2000

UPC Number:

66201921256

Status:

Active

Description:

120 VAC pluggable interface relay with 3 c/o without LED outputs and 250 V, 10A contact rating

Features

Switching of AC or DC loads with different resistive, inductive and capacitive parts, switching voltages from a few mV up to 250 V

Switching currents from a few mA up to 16 A

Amplification of weak control signals, electrical isolation of control and load circuits, and signal multiplying

Overload-proof against short-time variations like current or voltage peaks

Application

Link the electronic controlling PLC, PC or field bus system to the sensor/actuator level

General

Series	CR-U
Output Contacts	3PDT
Operation-Function	Control Relay

Dimension Information

L x W x D (inches)	1.38 x 1.38 x 2.14
--------------------	--------------------

Specifications

Rated Output Voltage (VDC)	250
Supply Voltage (DC)	12

Packaging

T&B Inner Pack	1
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	0.19 lbs. Each

Certifications

Approvals	UL
-----------	----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com