



## Monitoring Relays T&B Catalog Number:

1SVR730660R0100

**UPC Number:**

80432558388

**Status:**

Active

**Description:**

Insulation monitoring relay for ungrounded 0-250 VAC and 0-300 VDC systems with a maximum leakage capacitance of 10 microfarads and 24-240V AC/DC control supply voltage

### Features

- Measuring range 1-100 kilohms
- Selectable normally energized or normally de-energized
- Non-volatile fault storage configurable

### Application

Insulation monitoring relays for ungrounded IT installations

### General

Series	CM-S
Output Contacts	2 SPDT
Operation-Function	Insulation Monitor

### Dimension Information

L x W x D (inches)	3.07 x 1.77 x 3.94
--------------------	--------------------

### Specifications

Input Voltage (AC)	0-250
Input Voltage (DC)	0-300
Supply Voltage (AC)	24-240
Supply Voltage (DC)	24-240
LED Indicator	3
Time Delay	0.1 sec - 30 secs. Adjustable

### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	39.5 lbs. per 100

### Certifications

Approvals	CE
-----------	----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: techsupport@tnb.com