

Monitoring Relays T&B Catalog Number:

1SVR730760R0500

UPC Number: 80432558398

Status: Active

Description:

Window current monitoring relay, single phase with 24-240V AC/DC, sensitivity from 0.1-15 amps sensing range, and trip delay to 30 secs.

Selectable latching output Selectable normally energized or normally de-energized Application Window current monitoring General Series CM-S Output Contacts 2 SPDT Operation-Function Current Monitor Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) Supply Voltage (AC) Supply Voltage (DC) Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM Certifications Approvals UL	sitivity from 0.1-15 amps sensing range, and trip delay to 30 secs.	
Selectable normally energized or normally de-energized Application Window current monitoring General Series CM-S Output Contacts 2 SPDT Operation-Function Current Monitor Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Features	
Application Window current monitoring General Series CM-S Output Contacts 2 SPDT Operation-Function Current Monitor Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications		Selectable latching output
General Series CM-S Output Contacts 2 SPDT Operation-Function Current Monitor Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications		, ,
Series CM-S Output Contacts 2 SPDT Operation-Function Current Monitor Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Application	
Series CM-S Output Contacts 2 SPDT Operation-Function Current Monitor Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications		Window current monitoring
Output Contacts Operation-Function Current Monitor Dimension Information L x W x D (inches) Specifications Supply Voltage (AC) Supply Voltage (DC) Input Signal (A) LED Indicator Time Delay Packaging Package in Units 1 T&B Sold in UOM T&B Weight Per UOM Certifications Current Monitor 2 SPDT Current Monitor 2 4-240 3 .07 x 0.87 x 4.08 3 .07 x 0.87 x 4.08 2 4-240 2 4-240 3 .0 -3-15 LED Indicator 4 .1 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3	General	
Operation-Function Dimension Information L x W x D (inches) Specifications Supply Voltage (AC) Supply Voltage (DC) Input Signal (A) LED Indicator Time Delay Packaging Package in Units T&B Sold in UOM T&B Weight Per UOM Certifications Current Monitor 2.4-240 Current Monitor 3.07 x 0.87 x 4.08 24-240 24-240 0.3-15 1.7-10-10-10-10-10-10-10-10-10-10-10-10-10-	Series	CM-S
Dimension Information L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Output Contacts	2 SPDT
L x W x D (inches) 3.07 x 0.87 x 4.08 Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	•	Current Monitor
Specifications Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Dimension Information	
Supply Voltage (AC) 24-240 Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	L x W x D (inches)	3.07 x 0.87 x 4.08
Supply Voltage (DC) 24-240 Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging 1 Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Specifications	
Input Signal (A) 0.3-15 LED Indicator 3 Time Delay 0.1 sec - 30 secs. Adjustable Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications		
Time Delay Packaging Package in Units T&B Sold in UOM T&B Weight Per UOM Certifications 3 0.1 sec - 30 secs. Adjustable 1 1 42.5 lbs. per 100 Certifications		
Time Delay Packaging Package in Units T&B Sold in UOM T&B Weight Per UOM Certifications 0.1 sec - 30 secs. Adjustable 1 42.5 lbs. per 100		
Packaging Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM Certifications 1 42.5 lbs. per 100		
Package in Units 1 T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	•	0.1 sec - 30 secs. Adjustable
T&B Sold in UOM Each T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Packaging	
T&B Weight Per UOM 42.5 lbs. per 100 Certifications	Package in Units	1
Certifications	T&B Sold in UOM	Each
	•	42.5 lbs. per 100
Approvals UL	Certifications	
	Approvals	UL

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com