

Representative



Representative

Catalog Number: XPLFL318

 Product ID:
 7TAD013340R0012

 UPC Number:
 78620988442

 EAN Number:
 05415022259841

Status: Active

1 Inch x 18 Inch XP Flex Explosion Proof Flexible Coupling

- UL Listed for use in hazardous and wet locations.
- · Corrosion-resistant, ideal for washdown areas.
- Flexible bronze construction with arc-resistant inner sleeve and brass fittings.
- Terminated with two threaded female end fittings and male close nipples.
- No bonding jumper required.
- Flexible design allows for use to make tight bends or allow for movement or vibration.

North American Specifications (UNSPSC)		
UNSPSC	39131707 Electrical conduit coupling	
IGCC	5548 Electrical conduit coupling	
Brand Name	T&B	
Туре	XP Flex Explosion-Proof Flexible Couplings-Haz-	
	ardous Location	
Special Features	No Bonding Jumper Required	
Application	Explosion-Proof and Dust-Ignition-Proof for Use In	
	Hazardous Locations	
Standard	UL E193396, cULus	
Trade Size	1 Inch	
Length	18 in	
Material	Brass	
Color	Metallic	

European Specifications (ETIM)		
ETIM	EC000939 Coupler for installation tubes	
Material	Metal	
Material quality	Other	
Model	Thread	
Two piece	N	
With inspection opening and cover	N	

Packaging		
Outer Quantity	1	
Outer Dimensions (inches)	18x3x3	
Weight Llom	5.5 lbs Fach	

Documents / Support Tools	
Technical Drawing / Data Sheet	WSD-000382
Technical Drawing / Data Sheet Canada	Available on Website

Header	
3D Model	Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com