SIEMENS

Data sheet

6GK5008-0BA10-1AB2

SCALANCE XB008 Unmanaged Industrial Ethernet Switch for 10/100 Mbit/s for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 8x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download



Product type designation	SCALANCE XB008	
Transfer rate		
Transfer rate	10 Mbit/s, 100 Mbit/s	
Interfaces / for communication / Integrated		
Number of electrical connections		
 for network components or terminal equipment 	8; RJ45	
Number of 100 Mbit/s SC ports		
• for multimode	0	
Interfaces / other		
Number of electrical connections		
• for power supply	1	
Type of electrical connection		
• for power supply	3-pole terminal block	
Supply voltage, current consumption, power loss		
Type of voltage / of the supply voltage	AC/DC	
Supply voltage		
• external	24 V	

• external / minimum	19.2 V
external / maximum	28.8 V
• at AC	24 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.12 A
Power loss [W]	0.12 A
	2.88 W
• at DC / at 24 V	2.00 W
Ambient conditions	
Ambient temperature	
 during operation 	-10 +60 °C
 during storage 	-40 +80 °C
 during transport 	-40 +80 °C
Relative humidity	
• at 25 °C / without condensation / during	95 %
operation / maximum	
Protection class IP	IP20
Design, dimensions and weight	
Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.18 kg
Mounting type	
 35 mm DIN rail mounting 	Yes
 wall mounting 	Yes
• S7-1500 rail mounting	No
Product functions / management, configuration, eng Product function	gineering
multiport mirroring	No
	Yes
• CoS	
PROFINET conformity class Product function / switch managed	A
Product function / switch-managed	No
Product functions / redundancy	
Product function	
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No
Standards, specifications, approvals	
Standard	

• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
 for hazardous zone 	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
 for emitted interference 	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
MTBF	214 у

Standards,	specifications,	approvals / CE
Certificate	of suitability / CE	marking

Standards, specifications, approvals / other		
Certificate of suitability	EN 61000-6-2, EN 61000-6-4	
• C-Tick	Yes	
 KC approval 	Yes	
Further information / Internet-Links		

Yes

Internet-Link	
 to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
 to website: Industrial communication 	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx Download Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

02/12/2020