

SIDOOR M3 L geared motor, Pinion, left max. 180kg door weight,
Cable length 1.5 m, 30VDC, -20°C to +50°C



General information

Product type designation	M3 L
--------------------------	------

Supply voltage

Rated value (DC)	30 V
------------------	------

Input current

Operational current (rated value)	4 A
-----------------------------------	-----

Power

Active power input	120 W
--------------------	-------

Mechanical data

Torque of the rotary operating mechanism (rated value)	3 N·m
--	-------

Speed, max.	0.65 m/s
-------------	----------

Gear ratio	15
------------	----

Number of pulses per revolution, max.	100
---------------------------------------	-----

Weight of door, max.	180 kg
----------------------	--------

Degree and class of protection

IP degree of protection	
-------------------------	--

- of the motor
- of the gear unit

IP54

IP40

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes
EAC (formerly Gost-R)	Yes
TÜV Inspectorate approval	Yes
China RoHS compliance	Yes

Ambient conditions

Ambient temperature during operation	
• min.	-20 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• Storage, min.	-40 °C
• Storage, max.	85 °C

Dimensions

Height of motor	98 mm
Length of motor	236 mm
Diameter of motor	63 mm
Width of gear unit, including drive pinion	85 mm

last modified: 03/16/2020