

SIMATIC DP, ET 200ECO PN, 8 DO 24 V DC/0.5 A; 4xM12, Duplicate assignment, 1 load voltage supply DO; Degree of protection IP67



Figure similar

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Load voltage 2L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
from load voltage 2L+, max.	4 A
Power loss	
Power loss, typ.	3 W
Digital outputs	

Number of digital outputs	8
• in groups of	8
Short-circuit protection	Yes
• Response threshold, typ.	0.7 A
Limitation of inductive shutdown voltage to	Typ. (L1+, L2+) -47 V
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	1.5 mA
<b>Parallel switching of two outputs</b>	
• for uprating	No
• for redundant control of a load	Yes
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
<b>Total current of the outputs (per group)</b>	
all mounting positions	
— up to 60 °C, max.	4 A
<b>Cable length</b>	
• unshielded, max.	30 m
<b>Interfaces</b>	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
<b>1. Interface</b>	
<b>Interface types</b>	
• integrated switch	Yes
<b>Interface types</b>	
<b>M12 port</b>	
• Transmission procedure	100BASE-TX
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s
<b>Protocols</b>	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
<b>PROFINET IO Device</b>	
Services	

— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes
<b>Open IE communication</b>	
• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostic messages</b>	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; Green "ON" LED
• Wire-break in actuator cable	Yes
• Short-circuit	Yes
• Group error	Yes; Red/yellow "SF/MT" LED
<b>Potential separation</b>	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
<b>Potential separation channels</b>	
• between the channels	No
<b>Isolation</b>	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
<b>Degree and class of protection</b>	
IP degree of protection	IP67
<b>Standards, approvals, certificates</b>	
Suitable for safety-related tripping of standard modules	Yes
<b>Highest safety class achievable for safety-related tripping of standard modules</b>	
• Performance level according to ISO 13849-1	PL d
• Category according to ISO 13849-1	Cat. 3
• SILCL according to IEC 62061	SILCL 2
<b>Connection method</b>	

Design of electrical connection	4/5-pin M12 circular connectors
<b>Dimensions</b>	
Width	30 mm
Height	200 mm
Depth	49 mm
<b>Weights</b>	
Weight, approx.	550 g
<b>last modified:</b>	11/16/2019