SIEMENS

Data sheet 6GT2800-4BB00

Product type designation

RF340T transponder

SIMATIC RF300 Transponder RF340T 8 KB FRAM, IP67/X9K, -25 to +85 $^{\circ}\text{C},\,48x2\,5x\,15$ mm, Minimum order quantity 5 units



Suitability for operation

| Radio frequencies | |
|---|---|
| Operating frequency / Rated value | 13.56 MHz |
| Range / maximum | 105 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964 |
| Protocol / with radio transmission | RF300-specific |
| Transfer rate / with radio transmission / maximum | 106 kbit/s |
| Product feature / multitag-capable | Yes |

RF300

| Electrical data | |
|---|---|
| Product component / Backup battery | No |
| Type of memory | FRAM / EEPROM |
| Storage capacity / of the user memory | 8189 byte |
| Type of memory organization | UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes |
| Number of read cycles / at ambient temperature < 40 °C / maximum | 1000000000 |
| Number of write cycles / at ambient temperature < 40 °C / maximum | 1000000000 |

| Data retention time / at ambient temperature < 40 °C / not less than | 10 y |
|--|---|
| Property of memory | Block-by-block write protection of the OTP memory |
| Mechanical data | |
| Material | PA12 |
| Color | anthracite |
| Mounting distance / relating to metal surfaces / | 0 mm |
| recommended / minimum | |
| Ambient conditions | |
| Ambient temperature | |
| during read/write access | -25 +85 °C |
| outside the read/write area | -40 +85 °C |
| during storage | -40 +85 °C |
| Protection class IP | IP67 / IPx9K |
| Shock resistance | According to DIN EN 60721-3-7 Class 7 M3 |
| Shock acceleration | 500 m/s ² |
| Vibrational acceleration | 200 m/s² |
| Width | 25 mm |
| Height | 15 mm |
| Depth | 48 mm |
| Net weight | 25 g |
| Mounting type | 2 x M3 screws |
| Product features, product functions, product compo | nents / general |
| Product feature | |
| • silicon-free | Yes |
| • printable | No |
| Standards, specifications, approvals | |
| Certificate of suitability | |
| • IECEx | No |
| MTBF | 1200 y |
| Further information / Internet-Links | |
| Internet-Link | |
| • to website: Selector SIMATIC NET SELECTION TOOL | https://support.industry.siemens.com/cs/ww/en/view/67384964 |
| to website: Industrial communication | http://www.siemens.com/ident/rfid |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| to website: Information and Download Center | http://www.siemens.com/industry/infocenter |

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

http://www.siemens.com/cax

http://automation.siemens.com/bilddb

https://support.industry.siemens.com

last modified: 11/15/2019